

U.I. Lapp GmbH	<h1>DATASHEET</h1>	
	PKG shrink tube	61810850 14.11.2013

The PKG shrink tube with adhesive coating inside offers a good chemical resistance and high weather-resistance. The shrink ratio is 3:1.



Good chemical resistance



Flame-retardant



Mechanical resistance



Waterproof

Application range

Particularly suitable for corrosion and damp protected casings as well as highly contoured components

Benefits

Heat-resistant
 Good chemical resistance
 High mechanical stability
 Good weather-resistance
 High shrink ratio and adhesive coating

Product features

Adhesive lining bonds to plastic, rubber, neoprene, steel and polyethylene

Included

Cartons with 0.6 m units

Remark

Photographs are not to scale and do not represent detailed images of the respective products.



Product Management	Document: PKG shrink tube	1 / 2
--------------------	---------------------------	-------

U.I. Lapp GmbH	DATASHEET	
	PKG shrink tube	61810850 14.11.2013

Technical Data

Article description:	PKG 0301-0-C
Internal Ø before contraction (mm):	3
Shrinkage range (mm):	3 - 1
Panel thickness, shrunk +/- 0.1 mm:	1
PU (m):	12
PU:	1
Note:	Dielectric strength: 10 kV/mm
Info:	Shrinking ratio: 3:1 Length change during shrinking: maximum ±10 %
Colour delivered:	Black
Material:	Cross-linked modified polyolefin, with thermoplastic adhesive coating inside Silicone, Cadmium and Lead free
Temperature range:	-55°C to +110°C Shrinking temperature: +90°C

Product Management	Document: PKG shrink tube	2 / 2
--------------------	---------------------------	-------