

U.I. Lapp GmbH	DATASHEET	
	PKG shrink tube	61810870 14.11.2013

The PKG shrink tube with adhesive coating inside offers a good chemical resistance and high weather-resistance. The shrink ratio is 3:1.



Good chemical resistance



Flame-retardant



Mechanical resistance



Waterproof



Application range

Particularly suitable for corrosion and damp protected casings as well as highly contoured components

Benefits

- Heat-resistant
- Good chemical resistance
- High mechanical stability
- Good weather-resistance
- High shrink ratio and adhesive coating

Product features

Adhesive lining bonds to plastic, rubber, neoprene, steel and polyethylene

Included

Cartons with 0.6 m units

Remark

Photographs are not to scale and do not represent detailed images of the respective products.

Product Management	Document: PKG shrink tube	1 / 2
--------------------	---------------------------	-------

U.I. Lapp GmbH	DATASHEET	
	PKG shrink tube	61810870 14.11.2013

Technical Data

Article description:	PKG 0903-0-C
Internal Ø before contraction (mm):	9
Shrinkage range (mm):	9 - 3
Panel thickness, shrunk +- 0.1 mm:	1.4
PU (m):	6
PU:	1
Note:	Dielectric strength: 10 kV/mm
Info:	Shrinking ratio: 3:1 Length change during shrinking: maximum ±10 %
Colour delivered:	Black
Material:	Cross-linked modified polyolefin, with thermoplastic adhesive coating inside Silicone, Cadmium and Lead free
Temperature range:	-55°C to +110°C Shrinking temperature: +90°C

Product Management	Document: PKG shrink tube	2 / 2
--------------------	---------------------------	-------