

PICTURE	ITEM NO. (OPERATION TIME CHART)	CONTACT RATING	CONTROL OUTPUT		TIME RANGE	SPECIFICATIONS
			TIME-LIMIT CONTACT	INSTANTANEOUS CONTACT		
	EH-5110A (fig.1)	250V AC. 5A (P.F=1)	SPDT	—	1S, 3S, 6S, 10S, 30S, 60S, 3M, 6M, 10M, 30M, 60M, 3H, 6H, 10H.	<ul style="list-style-type: none"> • RATED VOLTAGE: AC 24V, 110V, 220V, 380V DC 12V, 24V • AC/DC 12 - 240V • OPERATION TIME CHART:
	EH-5120A (fig.2)		DPDT	—		
	EH-5130A (fig.3)		SPDT	SPDT		
	EH-5110B (fig.1)	250V AC. 16A (P.F=1)	SPDT	—		
	EH-5120B (fig.2)		DPDT	—		
	EH-5130B (fig.3)		SPDT	SPDT		
	EH-5210A (fig.1)	250V AC. 5A (P.F=1)	SPDT	—	Two time ranges second/minute selectable: 1S/1M, 3S/3M, 6S/6M, 10S/10M, 60S/60M	<ul style="list-style-type: none"> • RATED VOLTAGE: AC 24V, 110V, 220V, 380V DC 12V, 24V • AC/DC 12 - 240V • OPERATION TIME CHART:
	EH-5220A (fig.2)		DPDT	—		
	EH-5230A (fig.3)		SPDT	SPDT		
	EH-5210B (fig.1)	250V AC. 16A (P.F=1)	SPDT	—		
	EH-5220B (fig.2)		DPDT	—		
	EH-5230B (fig.3)		SPDT	SPDT		
	EH-521A□←Time series (fig.1)	250V AC. 5A (P.F=1)	SPDT	—	<ul style="list-style-type: none"> • Time series□: A: 1S/10S/1M/10M B: 3S/30S/3M/30M C: 6S/60S/6M/60M D: 1M/10M/1H/10H E: 3M/30M/3H/30H 	
	EH-522A□←Time series (fig.2)		DPDT	—		
	EH-521B□←Time series (fig.1)	250V AC. 16A (P.F=1)	SPDT	—		
	EH-522B□←Time series (fig.2)		DPDT	—		
	EH-5410A (fig.4)	250V AC. 5A (P.F=1)	SPDT	—	<ul style="list-style-type: none"> • Circulation mode • Two time ranges second/minute selectable: 1S/1M, 3S/3M, 6S/6M, 10S/10M, 60S/60M 	
	EH-5420A (fig.5)		DPDT	—		
	EH-5410B (fig.4)	250V AC. 16A (P.F=1)	SPDT	—		
	EH-5420B (fig.5)		DPDT	—		
	EH-532A□←Time series (fig.2 & fig.3)	250V AC. 5A (P.F=1)	<ul style="list-style-type: none"> • A/B output mode selectable. • A mode: time limit contact DPDT (fig.2) 		<ul style="list-style-type: none"> • Time series□: A: 1S/10S/1M/10M B: 3S/30S/3M/30M C: 6S/60S/6M/60M D: 1M/10M/1H/10H E: 3M/30M/3H/30H 	
	EH-532B□←Time series (fig.2 & fig.3)	250V AC. 16A (P.F=1)	<ul style="list-style-type: none"> • B mode: time limit contact SPDT and instantaneous contact SPDT (fig.3) 			

fig.1


fig.2

fig.3

fig.4

fig.5

• DIMENSIONS (mm)



• MOUNTING METHODS:
BY DIN RAIL (35 mm)