

CONTROL UNIT

Ø22mm






NEW



GENERAL CHARACTERISTICS

- CONFORMITY TO STANDARDS : IEC / EN60947-5-1
- NOMINAL THERMAL CURRENT : 10A
- NOMINAL INSULATION VOLTAGE : 600V
- AC-15 INDUCTIVE LOAD : 3A/240V AC
- DC-13 INDUCTIVE LOAD : 0.27A/250V DC
- AMBIENT TEMPERATURE : -25 °C ~ +70 °C
- MECHANICAL LIFE : 1 MILLION OPERATIONS (LATCHING MUSHROOM HEAD
PUSH BUTTONS : 300,000 OPERATIONS)

⌀22mm

| PICTURE | ITEM NO. & DESCRIPTION | COLOR |
|--|---|--|
|  FPB-BA FLAT PUSH BUTTON | ITEM NO. : FPB-BA1 CONTACT CONFIGURATION : 1 N/O | ● BLACK ● GREEN ● YELLOW ● BLUE |
| | ITEM NO. : FPB-BA2 CONTACT CONFIGURATION : 1 N/C | ● BLACK ● RED |
|  EPB-BL EXTENDED PUSH BUTTON | ITEM NO. : EPB-BL1 CONTACT CONFIGURATION : 1 N/O | ● BLACK ● GREEN ● YELLOW ● BLUE |
| | ITEM NO. : EPB-BL2 CONTACT CONFIGURATION : 1 N/C | ● BLACK ● RED |
|  MUSHROOM HEAD PUSH BUTTON SPRING RETURN | ITEM NO. : MPB-BC1 ⌀40mm ITEM NO. : MPB-BR1 ⌀60mm CONTACT CONFIGURATION : 1 N/O | ● BLACK ● GREEN ● YELLOW ● BLUE |
| | ITEM NO. : MPB-BC2 ⌀40mm ITEM NO. : MPB-BR2 ⌀60mm CONTACT CONFIGURATION : 1 N/C | ● RED |
|  LMB-BS MUSHROOM HEAD PUSH BUTTON LATCHING TURN TO RELEASE | ITEM NO. : LMB-BS4 ⌀30mm ITEM NO. : LMB-BS5 ⌀40mm ITEM NO. : LMB-BS6 ⌀60mm CONTACT CONFIGURATION : 1 N/C | ● RED |
|  LMB-BT5 MUSHROOM HEAD PUSH BUTTON PUSH PULL SYAY PUT | ITEM NO. : LMB-BT5 ⌀40mm CONTACT CONFIGURATION : 1 N/C | ● RED |