

CONTROL UNIT

Ø22mm




NEW



GENERAL CHARACTERISTICS

- CONFORMITY TO STANDARDS : IEC / EN60947-5-1
- NOMINAL THERMAL CURRENT : 10A
- NOMINAL INSULATION VOLTAGE : 600V
- AC-15 INDUCTIVE LOAD : 3A/240V AC
- DC-13 INDUCTIVE LOAD : 0.27A/250V DC
- AMBIENT TEMPERATURE : -25 °C ~ +70 °C
- MECHANICAL LIFE : 1 MILLION OPERATIONS (LATCHING MUSHROOM HEAD
PUSH BUTTONS : 300,000 OPERATIONS)

∅22mm

PICTURE	ITEM NO. & DESCRIPTION	COLOR
 <p>IDS-BW ILLUMINATED PUSH BUTTON NEON BULB</p>	<ul style="list-style-type: none"> ● ITEM NO. : IDS-BW ● CONTACT CONFIGURATION : 1 N/O , 1 N/C 1 N/O+ 1 N/C ● ACV : 110V, 220V, 380V BA9S NEON BULB 	<ul style="list-style-type: none"> ● RED ● YELLOW ● GREEN ● BLUE ○ WHITE
 <p>IRS-BW ILLUMINATED PUSH BUTTON LED BULB</p>	<ul style="list-style-type: none"> ● ITEM NO. : IRS-BW ● CONTACT CONFIGURATION : 1 N/O , 1 N/C 1 N/O+ 1 N/C ● ACV : 110V, 220V VIA INTEGRAL RESISTOR BA9S 24V LED BULB 	<ul style="list-style-type: none"> ● RED ● YELLOW ● GREEN ● BLUE ○ WHITE
 <p>SKOS-BK ILLUMINATED SELECTOR ACV : 110V , 220 , NEON BULB BA9S</p>	<p>2 POSITION STAY PUT</p>	<ul style="list-style-type: none"> ● CLEAR ● RED ● GREEN ● YELLOW ● BLUE
	<ul style="list-style-type: none"> ● ITEM NO. : SKOS-BK2 ● CONTACT CONFIGURATION : 1 N/O + 1 N/C 	
	<p>3 POSITION STAY PUT</p>	
	<ul style="list-style-type: none"> ● ITEM NO. : SKOS-BK3 ● CONTACT CONFIGURATION : 2 N/O 	
	<p>3 POSITION SPRING RETURN TO CENTER</p>	
<ul style="list-style-type: none"> ● ITEM NO. : SKOS-BK5 ● CONTACT CONFIGURATION : 2 N/O 		