



Standard Specification

Model		TH3M		TM48S				
Products								
Type		Surface	Plush	x				
Dimension		50Hx40 Wx57.5D	70Hx47 Wx57.5D	45Hx48Wx78D				
Mounting & Socket	Surface (N)	PF085A	x	P2CF-08				
	Plush (Y)	x	US08 or P3G-08	Y48 & P3G-08 or Y48& US08				
Full Time Range		A:1S,10S,1M,10M B:3S,30S,3M,30M C:6S,60S,6M,60M D:1M,10M,1H,10H E:3M,30M,3H,30H		A:1S,10S,1M,10M B:3S,30S,3M,30M C:6S,60S,6M,60M E:3M,30M,3H,30H				
Rated Voltage		DC(V): 12, 24 AC(V): 12, 24, 110, 220, 240, 50/60Hz		24V~240V AC/DC				
Contact	Mode	TH3M-N	TH3M-Y	TM48S -A	TM48S -B	TM48S -C	MODE A	MODE B
	Time Limit 1C	x	x	5A	x	5A	5A	x
	Time Limit 2C	5A	5A	x	5A	x	x	5A
	Instantaneous 1C	x	x	5A	x	x	5A	x
Mechanical Life		5x10 ⁶ times		10 ⁶ times				
Electrical Life		10 ⁵ times		10 ⁵ times				
Accuracy	Repeat ERROR	±1% max		±1% max				
	Setting ERROR	±10% max		±10% max				
	Voltage ERROR	±1% max		±1% max				
	Temp. ERROR	±2% max		±2% max				
Resetting time		0.1 sec max		0.1 sec max				
Consumed Power		2VA		2VA				
Ambient Temperature		-10°C~+55°C		-10°C~+55°C				
Ambient Humidity		45~85% RH		45~85% RH				
Weight		160g		180g				