

PRODUCT-DETAILS

CK1-11

CK1-11 Short Circuit Signaling Contact



Información General

| | |
|----------------------------|--|
| Tipo de producto extendido | CK1-11 |
| Código de producto | 1SAM301901R1001 |
| EAN | 4013614403927 |
| Descripción corta | CK1-11 Short Circuit Signaling Contact |
| Descripción larga | CK1-11 Short-Circuit Signaling Contact 1 NO + 1 NC |

Clasificación

| | |
|---------------------------|----------|
| Cantidad mínima de pedido | 2 piece |
| Código arancelario | 85365080 |

Descargas Populares

| | |
|------------------------------------|------------------------------------|
| Ficha técnica, información técnica | 1SBC100192C02-- |
| Instrucciones y manuales | 2CDC131027M6802 2CDC131081M6801 |

Dimensiones

| | |
|-------------------|-------|
| Ancho del product | 9 mm |
| Alto del producto | 90 mm |

| | |
|-------------------|----------|
| Largo del product | 78 mm |
| Peso del product | 0.035 kg |

Technical

| | |
|---|--|
| Terminal Type | Screw Terminals |
| Rated Operational Voltage | 690 V AC 600 V DC Main Circuit 690 V |
| Rated Operational Current AC-15 (I _e) | (24 V) 6 A (240 V) 4 A (690 V) 1 A (380 / 400 V) 3 A |
| Rated Operational Current DC-13 (I _e) | (24 V) 2 A (125 V) 0.55 A (250 V) 0.27 A (440 V) 0.15 A (600 V) 0.15 A |
| Rated Impulse Withstand Voltage (U _{imp}) | Auxiliary Circuit 6 kV |
| Rated Insulation Voltage (U _i) | 690 V |
| Grado de protección | IP20 |
| Electrical Durability | 10000 cycle |
| Mechanical Durability | 10000 cycle |
| Connecting Capacity Auxiliary Circuit | Flexible with Ferrule 1/2x 0.75 ... 1.5 mm ² Flexible with Insulated Ferrule 1/2x 0.75 ... 1.5 mm ² Flexible 1/2x 0.75 ... 1.5 mm ² Rigid 1/2x 1 ... 1.5 mm ² |
| Tightening Torque | Auxiliary Circuit 0.8 ... 1.2 N·m |
| Wire Stripping Length | Auxiliary Circuit 8 mm |
| Recommended Screw Driver | M3 Pozidriv 2 |
| Number of Auxiliary Contacts NO | 1 |
| Number of Auxiliary Contacts NC | 1 |
| Standards | CSA 22,2 No. 14 IEC/EN 60947-1 IEC/EN 60947-5-1 UL 508 UL 60947-1 UL 60947-5-1 |
| Product Name | Short Circuit Signaling Contact |
| Suitable For | MS132 MS165 |
| Suitable for Product Class | Manual Motor Starter |
| Accessory Group | Electrical |
| Accessory Type | Short Circuit Signaling Contact |

Technical UL/CSA

| | |
|--|--|
| Maximum Operating Voltage UL/CSA | Main Circuit 600 V AC |
| Connecting Capacity Auxiliary Circuit UL/CSA | Flexible 1/2x 16-14 AWG Stranded 1/2x 16-14 AWG |
| Tightening Torque UL/CSA | Auxiliary Circuit 7 in·lb |
| Contact Rating UL/CSA | B600 Q600 |

Ambiente

| | |
|---|--|
| Temperatura ambiente | Funcionamiento -25 ... +60 °C Almacenamiento -50 ... +80 °C |
| Resistance to Shock acc. to IEC 60068-2-27 | 11 ms Pulse 25g |
| Resistance to Vibrations acc. to IEC 60068-2-6 | 5g / 3 ... 150 Hz |
| RoHS Status | Following EU Directive 2011/65/EU |

Certificados y Declaraciones (Número de Documento)

| | |
|-------------------------------------|--|
| ABS Certificate | 1SAA963001-0101 |
| BV Certificate | 1SAA963002-0201 |
| CB Certificate | 1SAA963004-2002 |
| CQC Certificate | CQC2017010304032778 |
| cUL Certificate | cUL_E137861 |
| Declaration of Conformity - CCC | 2020980304001252 |
| Declaración de conformidad - CE | 1SAD938504-0196 1SAD938507-0190 1SAD938504-0198 1SAD938506-0197 1SAD938508-0188 1SAD938516-0125 |
| Declaration of Conformity - UKCA | 1SAD938502-1060 1SAD938503-1125 1SAD938503-1188 1SAD938503-1198 |
| DNV GL Certificate | 1SAA963001-0304 |
| Instrucciones y manuales | 2CDC131027M6802 2CDC131081M6801 |
| LR Certificate | 1SAA963001-0502 1SAA918001-0501 |
| RINA Certificate | 1SAA963002-0802 |
| RoHS Information | 1SAD938516-0125 |
| UL Certificate | UL_E137861 |

Información de Embalaje

| | |
|-----------------------------------|---------------|
| Embalaje Nivel 1 Ancho | 25 mm |
| Embalaje Nivel 1 Largo | 80 mm |
| Embalaje Nivel 1 Alto | 93 mm |
| Embalaje Nivel 1 Peso | 0.08 kg |
| Embalaje Nivel 1 EAN | 4013614481529 |
| Embalaje Nivel 1 Unidades | 2 piece |
| Package Level 2 Width | 280 mm |
| Package Level 2 Depth / Length | 395 mm |
| Package Level 2 Height | 210 mm |
| Package Level 2 EAN | 4013614526015 |
| Package Level 2 Units | 160 piece |

Clasificaciones

| | |
|-------------------------------|--|
| Object Classification Code | Q |
| ETIM 4 | EC002498 - Accessories for low-voltage switch technology |
| ETIM 5 | EC000041 - Auxiliary contact block |

| | |
|------------------------------------|------------------------------------|
| ETIM 6 | EC000041 - Auxiliary contact block |
| ETIM 7 | EC000041 - Auxiliary contact block |
| eClass | V11.0 : 27371302 |
| UNSPSC | 39121522 |
| IDEA Granular Category Code (IGCC) | 4742 >> Electrical contacts |
| E-Number (Finland) | 3706160 |
| E-Number (Sweden) | 3110145 |

Categorías

Productos y sistemas de baja tensión → Aparatos de control → Guardamotores → Manual Motor Starters Accessories

