

PRODUCT-DETAILS

TF65-28

TF65-28 Thermal Overload Relay



Información General

Tipo de producto extendido	TF65-28
Código de producto	1SAZ811201R1001
EAN	4013614482915
Descripción corta	TF65-28 Thermal Overload Relay
Descripción larga	The TF65-28 thermal overload relay is an economic electromechanical protection device for the main circuit. It offers reliable and fast protection for motors in the event of overload or phase failure. The device has trip class 10. Further features are the temperature compensation, trip contact (NC), signal contact (NO), automatic- or manual reset selectable, trip-free mechanism, STOP function and a trip indication. The overload relays are connected directly to the block contactors. Single mounting kits are available as accessory.

Clasificación

Cantidad mínima de pedido	1 piece
Código arancelario	85364900

Descargas Populares

Ficha técnica, información técnica	2CDC106069D0201
Data Sheet, Technical Information (Part 2)	1SAC200122W0001
Data Sheet, Technical Information (Part 3)	1SAZ800503 1SAZ800506

Instrucciones y manuales	2CDC106051M6803
Instructions and Manuals (Part 2)	2CDC106085M6801
Time-Current Characteristic Curve	1SAZ800502F0001
Dimension Diagram	1SAZ800401F0001

Dimensiones

Ancho del product	54.9 mm
Alto del producto	101.4 mm
Largo del product	106.9 mm
Peso del product	0.372 kg

Technical

Setting Range	22 ... 28 A
Rated Operational Voltage	Auxiliary Circuit 600 V AC/DC Main Circuit 690 V AC Main Circuit 440 V DC
Rated Operational Current (I_e)	28 A
Rated Operational Current AC-3 (I_e)	28 A
Rated Frequency (f)	Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC Main Circuit 50 Hz Main Circuit 60 Hz
Rated Impulse Withstand Voltage (U_{imp})	Auxiliary Circuit 6 kV Main Circuit 8 kV
Rated Insulation Voltage (U_i)	690 V
Number of Poles	3
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	1
Number of Protected Poles	3
Conventional Free-air Thermal Current (I_{th})	Auxiliary Circuit NC 6 A Auxiliary Circuit NO 4 A
Rated Operational Current AC-15 (I_e)	(120 V) NC 3 A (120 V) NO 0.5 A (240 V) NC 3 A (240 V) NO 0.5 A (400 V) NC 0.75 A (400 V) NO 0.5 A (500 V) NC 0.75 A (500 V) NO 0.5 A
Rated Operational Current DC-13 (I_e)	(125 V) NC 0.55 A (125 V) NO 0.55 A (24 V) NC 1.25 A (24 V) NO 1.25 A (250 V) NC 0.27 A (250 V) NO 0.27 A (500 V) NC 0.15 A (500 V) NO 0.15 A (60 V) NC 0.55 A (60 V) NO 0.55 A
Grado de protección	Housing IP20 Main Circuit Terminals IP10
Pollution Degree	3

Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1/2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 1x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 1.5 mm ² Flexible 1/2x 0.75 ... 1 mm ² Flexible 1/2x 1 ... 2.5 mm ² Rigid 1/2x 0.75 ... 4 mm ²
Connecting Capacity Main Circuit	Flexible with Ferrule 1/2x 2.5 ... 10 mm ² Flexible with Ferrule 1x 2.5 ... 35 mm ² Flexible with Insulated Ferrule 1x 2.5 ... 35 mm ² Flexible with Insulated Ferrule 1/2x 2.5 ... 10 mm ² Flexible 1/2x 2.5 ... 16 mm ² Flexible 1x 2.5 ... 35 mm ² Rigid 1/2x 2.5 ... 16 mm ² Rigid 1x 2.5 ... 35 mm ²
Tightening Torque	Auxiliary Circuit 1 ... 1.2 N·m Main Circuit 4.0 ... 4.5 N·m
Wire Stripping Length	Auxiliary Circuit 9 mm Main Circuit 17 mm
Recommended Screw Driver	Auxiliary Circuit Pozidriv 2 Main Circuit Pozidriv 2
Mounting Position	1 ... 6
Power Loss	at Rated Operating Conditions per Pole 1.9 ... 3.1 W
Suitable For	AF40 AF52 AF65
Standards	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 600 V AC
Ampere Rating UL/CSA	28 A
Contact Rating UL/CSA	(NC:) B600 (NC:) Q600 (NO:) Q600 (NO:) D300
Connecting Capacity Main Circuit UL/CSA	Flexible 1x 12-2 AWG Flexible 2x 12-6 AWG Stranded 1x 12-2 AWG Stranded 2x 12-6 AWG
Connecting Capacity Auxiliary Circuit UL/CSA	Flexible 1/2x 18-12 AWG Stranded 1/2x 18-12 AWG
Tightening Torque UL/CSA	Auxiliary Circuit 9 ... 11 in·lb Main Circuit 35 ... 40 in·lb

Ambiente

Temperatura ambiente	Funcionamiento -40 ... +70 °C Operation Compensated -40 ... +70 °C Almacenamiento -50 ... +80 °C
Ambient Air Temperature Compensation	Yes
Maximum Operating Altitude Permissible	2000 m
Resistance to Shock acc. to IEC 60068-2-27	11 ms Pulse 25g
Resistance to Vibrations acc. to IEC 60068-2-6	5g / 3 ... 150 Hz
RoHS Status	Following EU Directive 2011/65/EU

Certificados y Declaraciones (Número de Documento)

ABS Certificate	1SAA941003-0101
ATEX Certificate	1SAA941005-3901
BV Certificate	1SAA941001-0203
CB Certificate	1SAA941015-2001
CQC Certificate	CQC2014010309689432
cUL Certificate	cUL_E48139
Declaration of Conformity - CCC	2020980309000291
Declaración de conformidad - CE	1SAD938512-0187
Declaration of Conformity - UKCA	1SAD938501-1187
DNV GL Certificate	1SAA941004-0301
EAC Certificate	1SAA941002-2701
Environmental Information	1SAC200058H0009
IECEX Certificate	1SAA941001-4001
Instrucciones y manuales	2CDC106051M6803
Instructions and Manuals (Part 2)	2CDC106085M6801
LR Certificate	1SAA941003-0501
RINA Certificate	RINA_ELE098115XG
RMRS Certificate	1SAA941002-0701
RoHS Information	1SAD938512-0187
Time-Current Characteristic Curve	1SAZ800502F0001
UL Certificate	cUL_E48139

Información de Embalaje

Embalaje Nivel 1 Unidades	1 piece
Embalaje Nivel 1 Ancho	123 mm
Embalaje Nivel 1 Alto	121 mm
Embalaje Nivel 1 Largo	82 mm
Embalaje Nivel 1 Peso	0.456 kg
Embalaje Nivel 1 EAN	4013614482915
Package Level 2 Units	12 piece
Package Level 2 Width	280 mm
Package Level 2 Height	210 mm
Package Level 2 Depth / Length	395 mm
Package Level 2 Gross Weight	5.858 kg
Package Level 2 EAN	4013614485312

Clasificaciones

Object Classification Code	F
ETIM 4	EC000106 - Thermal overload relay
ETIM 5	EC000106 - Thermal overload relay
ETIM 6	EC000106 - Thermal overload relay
ETIM 7	EC000106 - Thermal overload relay
eClass	V11.0 : 27371501
UNSPSC	39121520

IDEA Granular Category
Code (IGCC)

5364 >> Overload relay

E-Number (Finland)	3706583
E-Number (Sweden)	3210263

Accessories

Identifier	Description	Type	Quantity	Unit Of Measure
1SAZ801901R1001	DB65 Single Mounting Kit	DB65	1	piece
1SAX101911R1001	DRS-F-01 Remote Reset Coil	DRS-F-01	1	piece
1SAX101911R1002	DRS-F-02 Remote Reset Coil	DRS-F-02	1	piece
1SAX101911R1003	DRS-F-03 Remote Reset Coil	DRS-F-03	1	piece
1SAX101911R1004	DRS-F-04 Remote Reset Coil	DRS-F-04	1	piece
1SAZ701904R1001	DRS-F-TF-01 Remote Coil	DRS-F-TF-01	1	piece
1SAZ701904R1002	DRS-F-TF-02 Remote Coil	DRS-F-TF-02	1	piece
1SAZ701904R1003	DRS-F-TF-03 Remote Coil	DRS-F-TF-03	1	piece
1SAZ701904R1004	DRS-F-TF-04 Remote Coil	DRS-F-TF-04	1	piece
1SAZ701903R1001	WRH-F Holder	WRH-F	1	piece
1SAZ701903R1011	WRB-400 Bowden Wire	WRB-400	1	piece
1SAZ701903R1012	WRB-600 Bowden Wire	WRB-600	1	piece
1SAZ701903R1013	WRB-1000 Bowden Wire	WRB-1000	1	piece
1SAZ701903R1030	WRBG Gasket	WRBG	1	piece
1SFA616162R1014	KPR3-101L Reset push button	KPR-101L	1	piece

Categorías

Productos y sistemas de baja tensión → Aparatos de control → Contactores → Relés térmicos

