

PRODUCT-DETAILS

TEF4-OFF

TEF4-OFF Frontal Electronic Timer



Información General

Tipo de producto extendido	TEF4-OFF
Código de producto	1SBN020114R1000
EAN	3471523130654
Descripción corta	TEF4-OFF Frontal Electronic Timer
Descripción larga	<p>TEF4 frontal electronic timers are used for realizing timing function and are available in ON-delay and OFF-delay versions.</p> <p>Compact solution in cabinet compared to separate timers</p> <p>TEF4 electronic timers are front-mounted and locked on AF contactors or NF contactor relays.</p> <p>A mechanical indicator allows to show the state of the contactor.</p> <p>Safe and cost-reduced wiring.</p> <p>TEF4 electronic timers are supplied by a direct plug-in parallel connection to the coil terminals A1 - A2 of the contactor or contactor relay. A varistor is integrated on the timer to offer a built-in protection against surges in the contactor coil.</p> <p>Available for a wide control voltage range 24...240 V AC/DC</p> <p>TEF4-ON or TEF4-OFF allow time-delayed functions up to 100 s in 3 distinct time ranges, independently of the control system. The time delay ranges are selected by a switch and the time delay can be adjusted by means of a rotary switch. The timing function is activated by closing or opening the device on which the timer is mounted.</p> <p>The OFF-delay version operates without additional control supply.</p>

Technical

Suitable For	<p>AF09</p> <p>AF09Z</p> <p>AF12</p> <p>AF12Z</p> <p>AF16</p> <p>AF16Z</p>
--------------	--

AF26
 AF26Z
 AF30
 AF30Z
 AF38
 AF38Z
 AF40
 AF52
 AF65
 AF80
 AF96
 AFC09
 AFC12
 AFC16
 AFC26
 AFC30
 AFC38
 NF22E
 NFZ22E
 NF31E
 NFZ31E
 NF40E
 NFZ40E
 NFC22E
 NFC31E
 NFC40E

Rated Operational Voltage	Auxiliary Circuit 240 V AC Auxiliary Circuit 24 V DC
Rated Insulation Voltage (U _i)	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 400 V acc. to UL/CSA 300 V
Rated Impulse Withstand Voltage (U _{imp})	4 kV
Rated Operational Current AC-15 (I _e)	(24 / 127 V) 3 A (220 / 240 V) 1.5 A
Rated Short-time Withstand Current Low Voltage (I _{cw})	for 0.1 s 8 A for 1 s 8 A
Rated Frequency (f)	Auxiliary Circuit 50 / 60 Hz
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts CO (SPDT)	0
Tightening Torque	Auxiliary Circuit 1.2 N·m
Timer Relay Type	OFF-Delay
Mounting Position	Mounting positions 1, 1 +/- 30°, 2, 3, 4, 5
Terminal Type	Screw Terminals

Ambiente

Temperatura ambiente	Close to Contactor for Storage -40 ... +80 °C Funcionamiento -25 ... +70 °C
Grado de protección	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20
Maximum Operating Altitude Permissible	Without Derating 2000 m
Resistance to Vibrations acc. to IEC 60068-2-6	5 ... 300 Hz 3 g Closed position / 2 g Open position
RoHS Status	Following EU Directive 2011/65/EU
Environmental Information	1SBD250192E1000

Technical UL/CSA

Tightening Torque	Auxiliary Circuit 11 in·lb
-------------------	----------------------------

UL/CSA

Pilot Duty UL/CSA

B300
R300

Dimensiones

Ancho del product	43 mm
Alto del producto	41.6 mm
Largo del product	67.7 mm
Peso del product	0.065 kg

Información de Embalaje

Embalaje Nivel 1 Unidades	box 1 piece
Embalaje Nivel 1 Ancho	82 mm
Embalaje Nivel 1 Alto	51 mm
Embalaje Nivel 1 Largo	56 mm
Embalaje Nivel 1 Peso	0.065 kg
Embalaje Nivel 1 EAN	3471523130654
Package Level 2 Units	box 80 piece
Package Level 2 Width	254 mm
Package Level 2 Height	200 mm
Package Level 2 Depth / Length	319 mm
Package Level 2 Gross Weight	5.2 kg

Clasificación

Cantidad mínima de pedido	1 piece
Código arancelario	85389091
E-Number (Finland)	3706000
E-Number (Sweden)	3210257

Certificados y Declaraciones (Número de Documento)

ABS Certificate	ABS_20-2060694-PDA
CB Certificate	CB_CN46281
CCC Certificate	CCC_2012010303572179
CQC Certificate	CQC2012010303572179
Declaration of Conformity - CCC	2020980303000172
Declaración de conformidad - CE	1SBD250008U1000
Environmental Information	1SBD250192E1000
Instrucciones y manuales	1SBC101026M6801
RoHS Information	1SBD250008U1000
UL Certificate	UL_20120717_E252354
UL Listing Card	UL_E252354

Descargas Populares

Instrucciones y

1SBC101026M6801

manuales

UL Listing Card

UL_E252354

Clasificaciones

ETIM 7	EC002060 - Timer block
ETIM 8	EC002060 - Timer block
Categoría RAEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	8538 90 91
UNSPSC	39121500
Object Classification Code	K

Categorías

Productos y sistemas de baja tensión → Aparatos de control → Contactores → Block Contactors Accessories

