


PRODUCT-DETAILS

# VEM4

## VEM4 Mechanical and Electrical Interlock Unit



### Información General

Tipo de producto extendido	VEM4
Código de producto	1SBN030111R1000
EAN	3471523130616
Descripción corta	VEM4 Mechanical and Electrical Interlock Unit
Descripción larga	<p>Mechanical and electrical interlock sets</p> <p>VEM4 mechanical and electrical interlock set for the interlocking of two AF contactors.</p> <p>VEM4 set includes a mechanical interlock unit VM4 with 2 fixing clips (BB4) and a VE4 electrical interlock block with A2-A2 connection.</p> <p>Fixing the electrical interlock block to the contactor front face connects the 2 built-in N.C. interlocking contacts with the two coils. VE4 block must be used with A2-A2 connection to respect the electrical connection diagram.</p>

### Technical

Suitable For	AF09 AF09Z AF12 AF12Z AF16 AF16Z AF26 AF26Z AF30 AF30Z AF38 AF38Z AFC09 AFC12 AFC16
--------------	---

AFC26  
 AFC30  
 AFC38  
 AF09B  
 AF09ZB  
 AF12B  
 AF12ZB  
 AF16B  
 AF16ZB  
 AF26B  
 AF26ZB  
 AF30B  
 AF30ZB  
 AF38B  
 AF38ZB

Rated Insulation Voltage (U <sub>i</sub> )	acc. to IEC 60947-5-1 and VDE 0110 (Gr. C) 690 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	6 kV
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	1
Tightening Torque	Auxiliary Circuit 1.2 N·m
Wire Stripping Length	Auxiliary Circuit 10 mm
Terminal Type	Screw Terminals

## Ambiente

Grado de protección	acc. to IEC 60529, IEC 60947-1, EN 60529 Auxiliary Terminals IP20
RoHS Status	Following EU Directive 2011/65/EU
Environmental Information	1SBD250142E1000

## Technical UL/CSA

Tightening Torque UL/CSA	Auxiliary Circuit 11 in·lb
--------------------------	----------------------------

## Dimensiones

Ancho del product	25 mm
Alto del producto	43 mm
Largo del product	31.6 mm
Peso del product	0.035 kg

## Información de Embalaje

Embalaje Nivel 1 Unidades	box 1 piece
Embalaje Nivel 1 Ancho	92 mm
Embalaje Nivel 1 Alto	46 mm
Embalaje Nivel 1 Largo	35 mm
Embalaje Nivel 1 Peso	0.035 kg
Embalaje Nivel 1 EAN	3471523130616
Package Level 2 Units	box 132 piece
Package Level 2 Gross Weight	4.62 kg
Package Level 3 Units	3168 piece

---

## Clasificación

---

Cantidad mínima de pedido	1 piece
Código arancelario	85389099
E-Number (Finland)	3706551
E-Number (Sweden)	3210004

---



---

## Certificados y Declaraciones (Número de Documento)

---

ABS Certificate	ABS_20-2060694-PDA
CB Certificate	CB_SE-93053
CQC Certificate	CQC2013010304651497
Declaration of Conformity - CCC	2020980304001259
Declaración de conformidad - CE	1SBD250007U1000
Environmental Information	1SBD250142E1000
GOST Certificate	GOST_POCCFR.ME77.B07175.pdf
Instrucciones y manuales	1SBC101028M6801
RINA Certificate	RINA_ELE084013XG
RoHS Information	1SBD250007U1000
UL Certificate	UL_20091124-E312527-6-1
UL Listing Card	UL_E312527

---



---

## Descargas Populares

---

Instrucciones y manuales	1SBC101028M6801
UL Listing Card	UL_E312527

---



---

## Clasificaciones

---

ETIM 7	EC001044 - Mechanic interlock for switch
ETIM 8	EC001044 - Mechanic interlock for switch
Categoría RAEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business
CN8	8538 90 99
UNSPSC	39120000

---



---

## Categorías

---

Productos y sistemas de baja tensión → Aparatos de control → Contactores → Block Contactors Accessories

