

PRODUCT-DETAILS

# OT200E03CP

## OT200E03CP CHANGE-OVER SWITCH



### Información General

Tipo de producto extendido	OT200E03CP
Código de producto	1SCA022771R7520
EAN	6417019251912
Descripción corta	OT200E03CP CHANGE-OVER SWITCH
Descripción larga	Including a black plastic IP65 I-0-II pistol type handle (see the table below), shaft and bolt set for the cable connection. Handle padlockable in the 0-position, door interlock in the I- and lipositions and when padlocked.

### Clasificación

Cantidad mínima de pedido	1 piece
Código arancelario	85365080
Country of Origin	Finland (FI)

### Descargas Populares

Ficha técnica, información técnica	1SCC303003C0201
Instrucciones y manuales	1SCC301040M0002

### Dimensiones

Ancho del product	170 mm
Alto del producto	150 mm
Largo del product	160 mm
Peso del product	3.1 kg 6.83 lb

## Technical

Rated Operational Current AC-21A ( $I_e$ )	(380 ... 415 V) 200 A (500 V) 200 A (690 V) 200 A
Rated Operational Current AC-22A ( $I_e$ )	(380 ... 415 V) 200 A (500 V) 200 A (690 V) 200 A
Rated Operational Current AC-23A ( $I_e$ )	(380 ... 415 V) 200 A (500 V) 200 A (690 V) 200 A
Rated Operational Current AC-31B ( $I_e$ )	(380 ... 415 V) 200 A
Rated Operational Current AC-33B ( $I_e$ )	(380 ... 415 V) 200 A
Rated Operational Power AC-23A ( $P_e$ )	(380 ... 415 V) 110 kW (500 V) 132 kW (690 V) 200 kW
Conventional Free-air Thermal Current ( $I_{th}$ )	q = 40 °C 200 A
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 200 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	12 kV
Rated Insulation Voltage ( $U_i$ )	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	for 1 s 8 kiloampere rms
Power Loss	4 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included Mechanical at the End of the Switch 03 (Left Side)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	3
Grado de protección	Front IP20
Terminal Width	20 mm
Tightening Torque	acc. IEC 60947-1 15 ... 22 N·m
Transition Type	Open

## Ambiente

Environmental Information	1SCC303050D0201
---------------------------	-----------------

## Certificados y Declaraciones (Número de Documento)

Declaración de conformidad - CE	1SCC303002D0202
Environmental Information	1SCC303050D0201
Instrucciones y manuales	1SCC301040M0002
RoHS Information	1SCC301149D0202

## Información de Embalaje

Embalaje Nivel 1 Unidades	1 piece
Embalaje Nivel 1 Ancho	160 mm
Embalaje Nivel 1 Largo	245 mm
Embalaje Nivel 1 Alto	185 mm
Embalaje Nivel 1 Peso	3.3 kg
Embalaje Nivel 1 EAN	6417019251912

## Clasificaciones

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
Categoría RAEE	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3641503

## Categorías

Productos y sistemas de baja tensión → Interruptores-seccionadores → Change-over and Transfer Switches → Interruptores seccionadores - SwitchLine

