

PRODUCT-DETAILS

OT315E03CP

OT315E03CP CHANGE-OVER SWITCH



Información General

Tipo de producto extendido	OT315E03CP
Código de producto	1SCA022772R6780
EAN	6417019251981
Descripción corta	OT315E03CP CHANGE-OVER SWITCH
Descripción larga	Including a black plastic IP65 I-0-II pistol type handle (see the table below), shaft and bolt set for the cable connection. Handle padlockable in the 0-position, door interlock in the I- and lipositions and when padlocked.

Clasificación

Cantidad mínima de pedido	1 piece
Código arancelario	85365080
Country of Origin	Finland (FI)

Descargas Populares

Ficha técnica, información técnica	1SCC303003C0201
Instrucciones y manuales	1SCC301041M0002

Dimensiones

Ancho del product	221 mm
Alto del producto	185 mm
Largo del product	203 mm
Peso del product	6 kg

Technical

Rated Operational Current AC-21A (I_e)	(380 ... 415 V) 315 A (500 V) 315 A (690 V) 315 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 315 A (500 V) 315 A (690 V) 315 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 315 A (500 V) 315 A (690 V) 315 A
Rated Operational Current AC-31B (I_e)	(380 ... 415 V) 315 A
Rated Operational Current AC-33B (I_e)	(380 ... 415 V) 315 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 160 kW (500 V) 220 kW (690 V) 315 kW
Conventional Free-air Thermal Current (I_{th})	q = 40 °C 315 A
Conventional Thermal Current (I_{the})	Fully Enclosed 315 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 15 kiloampere rms
Power Loss	6.5 W
Pollution Degree	3
Handle Color	Black
Handle Type	Handle and shaft included Mechanism at the End of the Switch 03 (Left Side)
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	3
Grado de protección	Front IP20
Terminal Width	25 mm
Tightening Torque	acc. IEC 60947-1 30 ... 44 N·m
Transition Type	Open

Ambiente

Environmental Information	1SCC303050D0201
---------------------------	-----------------

Certificados y Declaraciones (Número de Documento)

Declaración de conformidad - CE	1SCC303004D0202
Environmental Information	1SCC303050D0201
Instrucciones y manuales	1SCC301041M0002
RoHS Information	1SCC301149D0202

Información de Embalaje

Embalaje Nivel 1 Unidades	1 piece
Embalaje Nivel 1 Ancho	240 mm
Embalaje Nivel 1 Largo	270 mm
Embalaje Nivel 1 Alto	218 mm
Embalaje Nivel 1 Peso	6.4 kg
Embalaje Nivel 1 EAN	6417019251981

Clasificaciones

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
Categoría RAEE	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3641505

Categorías

Productos y sistemas de baja tensión → Interruptores-seccionadores → Change-over and Transfer Switches → Interruptores seccionadores - SwitchLine

