


PRODUCT-DETAILS

OTM160E3CM230C

OTM160E3CM230C MOTORIZED C/O SWITCH



Información General

Tipo de producto extendido	OTM160E3CM230C
Código de producto	1SCA022845R8610
EAN	6417019296524
Descripción corta	OTM160E3CM230C MOTORIZED C/O SWITCH
Descripción larga	Including a handle for manual operation, bolt kit with nut and washers for all terminals and male connectors for control circuits. Include a storage clip for the handle and spare fuses.

Clasificación

Cantidad mínima de pedido	1 piece
Código arancelario	85365080
Country of Origin	Finland (FI)

Descargas Populares

Ficha técnica, información técnica	1SCC303003C0201
Instrucciones y manuales	1SCC303002M0204

Dimensiones

Ancho del product	273 mm
Alto del producto	150 mm
Largo del product	197 mm
Peso del product	5.6 kg

Technical

Rated Operational Current AC-21A (I_e)	(380 ... 415 V) 160 A (500 V) 160 A (690 V) 160 A
Rated Operational Current AC-22A (I_e)	(380 ... 415 V) 160 A (500 V) 160 A (690 V) 160 A
Rated Operational Current AC-23A (I_e)	(380 ... 415 V) 160 A (500 V) 160 A (690 V) 160 A
Rated Operational Current AC-31B (I_e)	(380 ... 415 V) 160 A
Rated Operational Current AC-33B (I_e)	(380 ... 415 V) 160 A
Rated Operational Power AC-23A (P_e)	(380 ... 415 V) 90 kW (500 V) 110 kW (690 V) 160 kW
Conventional Free-air Thermal Current (I_{th})	$q = 40\text{ °C}$ 160 A
Conventional Thermal Current (I_{the})	Fully Enclosed 160 A
Rated Impulse Withstand Voltage (U_{imp})	12 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 8 kiloampere rms
Motor Operational Voltage	220 ... 240 V AC
Power Loss	2.4 W
Pollution Degree	3
Handle Color	Black
Handle Type	Direct mounted handle Mechanism at the End of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	3
Grado de protección	Front IP20
Transition Type	Open

Ambiente

Environmental Information	1SCC303036D0202
---------------------------	-----------------

Certificados y Declaraciones (Número de Documento)

Declaración de conformidad - CE	1SCC303012D0202
Environmental Information	1SCC303036D0202
Instrucciones y manuales	1SCC303002M0204
RoHS Information	1SCC303036D0202

Información de Embalaje

Embalaje Nivel 1 Unidades	1 piece
Embalaje Nivel 1 Ancho	215 mm
Embalaje Nivel 1 Largo	395 mm
Embalaje Nivel 1 Alto	215 mm
Embalaje Nivel 1 Peso	6.9 kg
Embalaje Nivel 1 EAN	6417019296524

Clasificaciones

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
Categoría RAEE	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3641695

Categorías

Productos y sistemas de baja tensión → Interruptores-seccionadores → Change-over and Transfer Switches → Motorized Change-over Switches

