

PRODUCT-DETAILS

# OTM400E3CM230C

## OTM400E3CM230C MOTORIZED C/O SWITCH



### Información General

Tipo de producto extendido	OTM400E3CM230C
Código de producto	1SCA022847R1630
EAN	6417019297842
Descripción corta	OTM400E3CM230C MOTORIZED C/O SWITCH
Descripción larga	Including a handle for manual operation, bolt kit with nut and washers for all terminals and male connectors for control circuits. Include a storage clip for the handle and spare fuses.

### Clasificación

Cantidad mínima de pedido	1 piece
Código arancelario	85365080
Country of Origin	Finland (FI)

### Descargas Populares

Ficha técnica, información técnica	1SCC303003C0201
Instrucciones y manuales	1SCC303002M0204

### Dimensiones

Ancho del product	323 mm
Alto del producto	185 mm
Largo del product	235 mm
Peso del product	8.2 kg

## Technical

Rated Operational Current AC-21A ( $I_e$ )	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Current AC-22A ( $I_e$ )	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Current AC-23A ( $I_e$ )	(380 ... 415 V) 400 A (500 V) 400 A (690 V) 400 A
Rated Operational Current AC-31B ( $I_e$ )	(380 ... 415 V) 400 A
Rated Operational Current AC-33B ( $I_e$ )	(380 ... 415 V) 400 A
Rated Operational Power AC-23A ( $P_e$ )	(380 ... 415 V) 220 kW (500 V) 280 kW (690 V) 400 kW
Conventional Free-air Thermal Current ( $I_{th}$ )	q = 40 °C 400 A
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 400 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	12 kV
Rated Insulation Voltage ( $U_i$ )	1000 V
Rated Operational Voltage	1000 V
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	for 1 s 15 kiloampere rms
Motor Operational Voltage	220 ... 240 V AC
Power Loss	10 W
Pollution Degree	3
Handle Color	Black
Handle Type	Direct mounted handle Mechanism at the End of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	3
Grado de protección	Front IP20
Transition Type	Open

## Ambiente

Environmental Information	1SCC303036D0202
---------------------------	-----------------

## Certificados y Declaraciones (Número de Documento)

Declaración de conformidad - CE	1SCC303013D0202
Environmental Information	1SCC303036D0202
Instrucciones y manuales	1SCC303002M0204
RoHS Information	1SCC303036D0202

## Información de Embalaje

Embalaje Nivel 1 Unidades	1 pieza
Embalaje Nivel 1 Ancho	255 mm
Embalaje Nivel 1 Largo	460 mm
Embalaje Nivel 1 Alto	243 mm
Embalaje Nivel 1 Peso	10.22 kg
Embalaje Nivel 1 EAN	6417019297842

## Clasificaciones

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnecter
ETIM 6	EC000216 - Switch disconnecter
ETIM 7	EC000216 - Switch disconnecter
ETIM 8	EC000216 - Switch disconnecter
UNSPSC	39122217
Categoría RAEE	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3641752

## Categorías

Productos y sistemas de baja tensión → Interruptores-seccionadores → Change-over and Transfer Switches → Motorized Change-over Switches

