

PRODUCT-DETAILS

# OTM63F3CMA230V

## OTM63F3CMA230V MOTORIZED C/O SWITCH



### Información General

Tipo de producto extendido	OTM63F3CMA230V
Código de producto	1SCA120095R1001
EAN	6417019516844
Descripción corta	OTM63F3CMA230V MOTORIZED C/O SWITCH
Descripción larga	Including a handle for manual operation, bolt kit with nut and washers for all terminals and male connectors for control circuits. Types OTM630...2500E_ include a storage clip for the handle and spare fuses.

### Clasificación

Cantidad mínima de pedido	1 piece
Código arancelario	85365080
Country of Origin	Finland (FI)

### Descargas Populares

Ficha técnica, información técnica	1SCC303003C0201
Instrucciones y manuales	1SCC303009M0202

### Dimensiones

Ancho del product	230 mm
Alto del producto	100 mm
Largo del product	116 mm
Peso del product	1.64 kg

## Technical

Rated Operational Current AC-21A ( $I_e$ )	(380 ... 415 V) 63 A (500 V) 63 A (690 V) 63 A
Rated Operational Current AC-22A ( $I_e$ )	(380 ... 415 V) 63 A (500 V) 63 A (690 V) 63 A
Rated Operational Current AC-23A ( $I_e$ )	(380 ... 415 V) 63 A (500 V) 60 A (690 V) 40 A
Rated Operational Current AC-31B ( $I_e$ )	(380 ... 415 V) 63 A
Rated Operational Current AC-33B ( $I_e$ )	(380 ... 415 V) 63 A
Rated Operational Power AC-23A ( $P_e$ )	(380 ... 415 V) 30 kW (500 V) 37 kW (690 V) 37 kW
Conventional Free-air Thermal Current ( $I_{th}$ )	q = 40 °C 63 A
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 63 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	8 kV
Rated Insulation Voltage ( $U_i$ )	800 V
Rated Operational Voltage	800 V
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	for 1 s 2.5 kiloampere rms
Motor Operational Voltage	110 ... 240 V AC/DC
Power Loss	2.8 W
Pollution Degree	3
Handle Color	Black
Handle Type	Direct mounted handle Mechanism at the End of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	3
Cable Cross-Section	10-70 mm <sup>2</sup>
Grado de protección	Front IP20
Transition Type	Open

## Certificados y Declaraciones (Número de Documento)

Declaración de conformidad - CE	1SCC303039D0201
Instrucciones y manuales	1SCC303009M0202
RoHS Information	1SCC303036D0202

---

## Información de Embalaje

---

Embalaje Nivel 1 Unidades	1 piece
Embalaje Nivel 1 Ancho	115 mm
Embalaje Nivel 1 Largo	315 mm
Embalaje Nivel 1 Alto	115 mm
Embalaje Nivel 1 Peso	1.64 kg
Embalaje Nivel 1 EAN	6417019516844

---



---

## Clasificaciones

---

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
ETIM 8	EC000216 - Switch disconnector
UNSPSC	39122214
Categoría RAEE	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3601228

---



---

## Categorías

---

Productos y sistemas de baja tensión → Interruptores-seccionadores → Change-over and Transfer Switches → Motorized Change-over Switches

