

PRODUCT-DETAILS

# OTM40F3CMA230V

## OTM40F3CMA230V MOTORIZED C/O SWITCH



### General Information

Extended Product Type	OTM40F3CMA230V
Product ID	1SCA120096R1001
EAN	6417019516851
Catalog Description	OTM40F3CMA230V MOTORIZED C/O SWITCH
Long Description	Including a handle for manual operation, bolt kit with nut and washers for all terminals and male connectors for control circuits. Types OTM630...2500E_ include a storage clip for the handle and spare fuses.

### Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85365080
Country of Origin	Finland (FI)

### Popular Downloads

Data Sheet, Technical Information	1SCC303003C0201
Instructions and Manuals	1SCC303009M0202

### Dimensions

Product Net Width	230 mm
-------------------	--------

Product Net Height	100 mm
Product Net Depth / Length	116 mm
Product Net Weight	1.64 kg

## Technical

Rated Operational Current AC-21A ( $I_e$ )	(380 ... 415 V) 40 A (500 V) 40 A (690 V) 40 A
Rated Operational Current AC-22A ( $I_e$ )	(380 ... 415 V) 40 A (500 V) 40 A (690 V) 40 A
Rated Operational Current AC-23A ( $I_e$ )	(380 ... 415 V) 40 A (500 V) 40 A (690 V) 40 A
Rated Operational Current AC-31B ( $I_e$ )	(380 ... 415 V) 40 A
Rated Operational Current AC-33B ( $I_e$ )	(380 ... 415 V) 40 A
Rated Operational Power AC-23A ( $P_e$ )	(380 ... 415 V) 18.5 kW (500 V) 22 kW (690 V) 37 kW
Conventional Free-air Thermal Current ( $I_{th}$ )	q = 40 °C 40 A
Conventional Thermal Current ( $I_{the}$ )	Fully Enclosed 40 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	8 kV
Rated Insulation Voltage ( $U_i$ )	800 V
Rated Operational Voltage	800 V
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	for 1 s 2.5 kiloampere rms
Motor Operational Voltage	110 ... 240 V AC/DC
Power Loss	1.6 W
Pollution Degree	3
Handle Color	Black
Handle Type	Direct mounted handle Mechanism at the End of the Switch
Distance Between Phases	Standard
Position of Line Terminals	Top In - Bottom Out, Bottom In - Top Out
Operating Mode	Front operated
Mounting Type	Base mounting
Number of Poles	3
Cable Cross-Section	2.5-16 mm <sup>2</sup>
Degree of Protection	Front IP20
Transition Type	Open

## Certificates and Declarations (Document Number)

Declaration of Conformity - CE	1SCC303039D0201
Instructions and Manuals	1SCC303009M0202
RoHS Information	1SCC303036D0202

---

## Container Information

---

Package Level 1 Units	1 piece
Package Level 1 Width	115 mm
Package Level 1 Depth / Length	315 mm
Package Level 1 Height	115 mm
Package Level 1 Gross Weight	1.64 kg
Package Level 1 EAN	6417019516851

---

## Classifications

---

Object Classification Code	Q
ETIM 5	EC000216 - Switch disconnector
ETIM 6	EC000216 - Switch disconnector
ETIM 7	EC000216 - Switch disconnector
ETIM 8	EC000216 - Switch disconnector
UNSPSC	39122214
WEEE Category	5. Small Equipment (No External Dimension More Than 50 cm)
E-Number (Finland)	3601226

---

## Categories

---

Low Voltage Products and Systems → Switches → Change-over and Transfer Switches → Motorized Change-over Switches

