

PRODUCT-DETAILS

T4N 320 PR221DS-LS/I In=320 3p F F

T4N 320 PR221DS-LS/I In=320 3p F F



Información General

| | |
|----------------------------|---|
| Tipo de producto extendido | T4N 320 PR221DS-LS/I In=320 3p F F |
| Código de producto | 1SDA054117R1 |
| EAN | 8015644552169 |
| Descripción corta | T4N 320 PR221DS-LS/I In=320 3p F F |
| Descripción larga | C.BREAKER TMAX T4N 320 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC PR221DS-LS/I R 320 |

Clasificación

| | |
|---------------------------|---------------|
| E-Number (Sweden) | 3180305 |
| EAN | 8015644552169 |
| Cantidad mínima de pedido | 1 piece |
| Código arancelario | 85362090 |

Dimensiones

| | |
|-------------------|----------|
| Ancho del product | 105 mm |
| Alto del producto | 205 mm |
| Largo del product | 103.5 mm |
| Peso del product | 3.639 kg |

Información de Embalaje

| | |
|---------------------------|---------------|
| Embalaje Nivel 1 Unidades | 1 pieza |
| Embalaje Nivel 1 Ancho | 248 mm |
| Embalaje Nivel 1 Alto | 240 mm |
| Embalaje Nivel 1 Largo | 285 mm |
| Embalaje Nivel 1 Peso | 3.5 kg |
| Embalaje Nivel 1 EAN | 8015644552169 |

Ambiente

| | |
|-------------|--|
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
|-------------|--|

Información Adicional

| | |
|---|--|
| Electrical Durability | 6000 cycle 120 cycles per hour |
| Mechanical Durability | 20000 cycle 240 cycles per hour |
| Number of Poles | 3 |
| Power Loss | at Rated Operating Conditions per Pole 17.6 W |
| Product Main Type | SACE Tmax T |
| Product Name | Moulded Case Circuit Breaker |
| Product Type | CB |
| Rated Current (I_n) | Main Circuit 320 A |
| Rated Impulse Withstand Voltage (U_{imp}) | 8 kV |
| Rated Insulation Voltage (U_i) | 1000 V |
| Rated Operational Voltage | 690 V AC |
| Rated Service Short-Circuit Breaking Capacity (I_{cs}) | (220 V AC) 70 kA (230 V AC) 70 kA (380 V AC) 36 kA (400 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 30 kA (500 V AC) 25 kA (690 V) 20 kA |
| Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}) | (220 V AC) 70 kA (230 V AC) 70 kA (380 V AC) 36 kA (400 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 30 kA (500 V AC) 25 kA (690 V AC) 20 kA |
| Rated Uninterrupted Current (I_u) | 320 A |
| Release | PR221DS-LS/I |
| Release Type | EL |
| Short-Circuit Performance Level | N |
| Standards | IEC 60947 |
| Sub-type | T4 |
| Suitable For | T4 |
| Suitable for Product Class | Moulded Case Circuit Breakers |
| Terminal Connection Type | Fixed Circuit-Breakers Front |

| | |
|---|--------|
| Test Voltage Max (U_{test}) | 3500 V |
| Test Voltage at Industrial Frequency for 1 Minute | 3500 V |
| Version | F |

Certificados y Declaraciones (Número de Documento)

| | |
|------------------------------------|-----------------|
| Ficha técnica, información técnica | 1SDC210004D0203 |
| Declaración de conformidad - CE | 1SDL000165R0004 |
| Environmental Information | 9AKK10103A1057 |
| Instrucciones y manuales | 1SDH000436R0001 |
| Instructions and Manuals (Part 2) | ITSCE-RH0100001 |
| REACH Declaration | 9AKK108466A1425 |
| RoHS Information | 9AKK108466A1424 |

Clasificaciones

| | |
|----------------------------|--|
| ETIM 4 | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| ETIM 5 | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| ETIM 6 | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| ETIM 7 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| Object Classification Code | Q |
| UNSPSC | 39121100 |
| Categoría RAEE | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categorías

Productos y sistemas de baja tensión → Interruptores automáticos → Interruptores automáticos en caja moldeada → Tmax T

