

PRODUCT-DETAILS

T8L 2000 PR331/P LSI In=2000A 3p F F

T8L 2000 PR331/P LSI In=2000A 3p F F



Información General

Tipo de producto extendido	T8L 2000 PR331/P LSI In=2000A 3p F F
Código de producto	1SDA065723R1
EAN	8015644686307
Descripción corta	T8L 2000 PR331/P LSI In=2000A 3p F F
Descripción larga	C.BREAKER TMAX T8L 2000 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC PR331/P-LSI R 2000

Clasificación

EAN	8015644686307
Cantidad mínima de pedido	1 piece
Código arancelario	85362090
Order Code US and Canada	T8LFD3GC000000XX

Dimensiones

Ancho del product	427 mm
Alto del producto	382 mm
Largo del product	282 mm
Peso del product	9.7 kg

Información de Embalaje

Embalaje Nivel 1 Unidades	1 pieza
Embalaje Nivel 1 Ancho	525 mm
Embalaje Nivel 1 Alto	475 mm
Embalaje Nivel 1 Largo	695 mm
Embalaje Nivel 1 Peso	11.2 kg
Embalaje Nivel 1 EAN	8015644686307

Ambiente

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

Información Adicional

Electrical Durability	4500 cycle 20 cycles per hour
Mechanical Durability	15000 cycle 60 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 46 W
Product Main Type	SACE Tmax T
Product Name	Moulded Case Circuit Breaker
Product Type	CB
Rated Current (I_n)	2000 A
Rated Impulse Withstand Voltage (U_{imp})	8 kV
Rated Insulation Voltage (U_i)	1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 85 kA (400 V AC) 85 kA (415 V AC) 85 kA (440 V AC) 85 kA (500 V AC) 65 kA (690 V AC) 50 kA
Rated Short-time Withstand Current Low Voltage (I_{cw})	for 1 s 40 A
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 85 kA (400 V AC) 85 kA (415 V AC) 85 kA (440 V AC) 85 kA (500 V AC) 65 kA (690 V AC) 50 kA
Rated Uninterrupted Current (I_u)	2000 A
Release	PR232/P-LSI
Release Type	EL
Short-Circuit Performance Level	L
Standards	IEC 60947
Sub-type	T8
Terminal Connection Type	Fixed Circuit-Breakers Front

Version

F

Certificados y Declaraciones (Número de Documento)

Ficha técnica, información técnica	1SDC210023D0201
Declaración de conformidad - CE	1SDL000165R0008
Environmental Information	9AKK107046A3003
Instrucciones y manuales	1SDC210033D0202
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424

Clasificaciones

ETIM 4	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 5	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 6	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
Categoría RAEE	5. Small Equipment (No External Dimension More Than 50 cm)

Categorías

Productos y sistemas de baja tensión → Interruptores automáticos → Interruptores automáticos en caja moldeada → Tmax T

