

PRODUCT-DETAILS

# T8L 3200 PR331/P LSI In=3200A 3p F VR

## T8L 3200 PR331/P LSI In=3200A 3p F VR



### Información General

Tipo de producto extendido	T8L 3200 PR331/P LSI In=3200A 3p F VR
Código de producto	1SDA065734R1
EAN	8015644686413
Descripción corta	T8L 3200 PR331/P LSI In=3200A 3p F VR
Descripción larga	C.BREAKER TMAX T8L 3200 FIXED THREE-POLE WITH TERMINALS REAR VERTICAL AND SOLID-STATE RELEASE IN AC PR331/P-LSI R 3200

### Clasificación

EAN	8015644686413
Cantidad mínima de pedido	1 piece
Código arancelario	85362090
Order Code US and Canada	T8LFF3JC000000XX

### Dimensiones

Ancho del product	427 mm
Alto del producto	382 mm
Largo del product	282 mm
Peso del product	94 kg

## Información de Embalaje

Embalaje Nivel 1 Unidades	1 pieza
Embalaje Nivel 1 Ancho	525 mm
Embalaje Nivel 1 Alto	665 mm
Embalaje Nivel 1 Largo	695 mm
Embalaje Nivel 1 Peso	13.2 kg
Embalaje Nivel 1 EAN	8015644686413

## Ambiente

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

## Información Adicional

Electrical Durability	3000 cycle 20 cycles per hour
Mechanical Durability	15000 cycle 60 cycles per hour
Number of Poles	3
Power Loss	at Rated Operating Conditions per Pole 117 W
Product Main Type	SACE Tmax T
Product Name	Moulded Case Circuit Breaker
Product Type	CB
Rated Current ( $I_n$ )	3200 A
Rated Impulse Withstand Voltage ( $U_{imp}$ )	8 kV
Rated Insulation Voltage ( $U_i$ )	1000 V
Rated Operational Voltage	690 V AC
Rated Service Short-Circuit Breaking Capacity ( $I_{cs}$ )	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 85 kA (400 V AC) 85 kA (415 V AC) 85 kA (440 V AC) 85 kA (500 V AC) 65 kA (690 V AC) 50 kA
Rated Short-time Withstand Current Low Voltage ( $I_{cw}$ )	for 1 s 40 A
Rated Ultimate Short-Circuit Breaking Capacity ( $I_{cu}$ )	(220 V AC) 85 kA (230 V AC) 85 kA (380 V AC) 85 kA (400 V AC) 85 kA (415 V AC) 85 kA (440 V AC) 85 kA (500 V AC) 65 kA (690 V AC) 50 kA
Rated Uninterrupted Current ( $I_u$ )	3200 A
Release	PR232/P-LSI
Release Type	EL
Short-Circuit Performance Level	L
Standards	IEC 60947
Sub-type	T8
Terminal Connection Type	Fixed Circuit-Breakers Rear flat Vertical

Version

F

---

## Certificados y Declaraciones (Número de Documento)

---

Ficha técnica, información técnica	1SDC210023D0201
Declaración de conformidad - CE	1SDL000165R0008
Environmental Information	9AKK107046A3003
Instrucciones y manuales	1SDC210033D0202
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424

---

## Clasificaciones

---

ETIM 4	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 5	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 6	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
Categoría RAEE	4. Large Equipment (Any External Dimension More Than 50 cm)

---

## Categorías

---

Productos y sistemas de baja tensión → Interruptores automáticos → Interruptores automáticos en caja moldeada → Tmax T

