

PRODUCT-DETAILS

A1A 125 TMF 20-400 3p F F

A1A 125 TMF 20-400 3p F F



Información General

| | |
|----------------------------|---|
| Tipo de producto extendido | A1A 125 TMF 20-400 3p F F |
| Código de producto | 1SDA066511R1 |
| EAN | 8015644004231 |
| Descripción corta | A1A 125 TMF 20-400 3p F F |
| Descripción larga | C.BREAKER FORMULA A1A 125 FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMF R 20-400 A |

Clasificación

| | |
|---------------------------|---------------|
| EAN | 8015644004231 |
| Cantidad mínima de pedido | 1 piece |
| Código arancelario | 85362090 |
| Order Code US and Canada | AAA020TW |

Dimensiones

| | |
|-------------------|---------|
| Ancho del product | 76.2 mm |
| Alto del producto | 130 mm |
| Largo del product | 60 mm |
| Peso del product | 0.78 kg |

Información de Embalaje

| | |
|---------------------------|---------------|
| Embalaje Nivel 1 Unidades | 1 pieza |
| Embalaje Nivel 1 Ancho | 136.5 mm |
| Embalaje Nivel 1 Alto | 124 mm |
| Embalaje Nivel 1 Largo | 110.5 mm |
| Embalaje Nivel 1 Peso | 0.8 kg |
| Embalaje Nivel 1 EAN | 8015644004231 |

Ambiente

| | |
|-------------|--|
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
|-------------|--|

Información Adicional

| | |
|---|---|
| Electrical Durability | 1500 cycle |
| Mechanical Durability | Nr. Operations 8500 cycle |
| Number of Poles | 3 |
| Opening Time | CB with SOR 15 ms CB with UVR 15 ms |
| Power Loss | at Rated Operating Conditions per Pole 3 W |
| Product Main Type | SACE FORMULA |
| Product Name | Moulded Case Circuit Breaker |
| Product Type | CB |
| Rated Current (I_n) | Main Circuit 20 A |
| Rated Impulse Withstand Voltage (U_{imp}) | 6 kV |
| Rated Insulation Voltage (U_i) | 690 V |
| Rated Operational Voltage | 550 V AC 250 V DC |
| Rated Service Short-Circuit Breaking Capacity (I_{cs}) | (240 V AC) 12.5 kA (380 V AC) 5 kA (415 V AC) 5 kA (440 V AC) 4 kA (480 V AC) 3.75 kA (500 V AC) 2.5 kA (250 V DC) 2 Poles in Series 2.5 kA |
| Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}) | (240 V AC) 10 kA (380 V AC) 10 kA (415 V AC) 10 kA (440 V AC) 8 kA (480 V AC) 7.5 kA (500 V AC) 5 kA (250 V DC) 5 kA |
| Rated Uninterrupted Current (I_u) | 125 A |
| Release | TMF |
| Release Type | TM |
| Short-Circuit Performance Level | A |
| Standards | IEC |
| Sub-type | A1 |
| Terminal Connection Type | Front |
| Version | F |

Certificados y Declaraciones (Número de Documento)

| | |
|------------------------------------|-----------------|
| Ficha técnica, información técnica | 1SDC210032D0204 |
| Declaración de conformidad - CE | 9AKK106713A5519 |
| Environmental Information | 1SDL000183R0001 |
| Instrucciones y manuales | 1SDH000717R0001 |
| REACH Declaration | 9AKK108466A1425 |
| RoHS Information | 9AKK108466A1424 |

Clasificaciones

| | |
|----------------------------|--|
| ETIM 4 | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| ETIM 5 | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| ETIM 6 | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| ETIM 7 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| Object Classification Code | Q |
| Categoría RAEE | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categorías

Productos y sistemas de baja tensión → Interruptores automáticos → Interruptores automáticos en caja moldeada → Formula DSA

