

PRODUCT-DETAILS

A3N 400 TMF 320-3200 3p F F

A3N 400 TMF 320-3200 3p F F



Información General

Tipo de producto extendido	A3N 400 TMF 320-3200 3p F F
Código de producto	1SDA066560R1
EAN	8015644693299
Descripción corta	A3N 400 TMF 320-3200 3p F F
Descripción larga	C.BREAKER FORMULA A3N 400 FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMF R 320-3200 A

Clasificación

EAN	8015644693299
Cantidad mínima de pedido	1 piece
Código arancelario	85362090
Order Code US and Canada	ACN320TW

Dimensiones

Ancho del product	139.5 mm
Alto del product	205 mm
Largo del product	103.5 mm

Peso del product	4.592 kg
------------------	----------

Información de Embalaje

Embalaje Nivel 1 Unidades	1 piece
Embalaje Nivel 1 Ancho	286 mm
Embalaje Nivel 1 Alto	228 mm
Embalaje Nivel 1 Largo	244 mm
Embalaje Nivel 1 Peso	4.85 kg
Embalaje Nivel 1 EAN	8015644693299

Ambiente

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

Información Adicional

Electrical Durability	2000 cycle
Mechanical Durability	Nr. Operations 5000 cycle
Number of Poles	3
Opening Time	CB with SOR 15 ms CB with UVR \leq 25 ms
Power Loss	at Rated Operating Conditions per Pole 13.6 W
Product Main Type	SACE FORMULA
Product Name	Moulded Case Circuit Breaker
Product Type	CB
Rated Current (I_n)	Main Circuit 320 A
Rated Impulse Withstand Voltage (U_{imp})	6 kV
Rated Insulation Voltage (U_i)	690 V
Rated Operational Voltage	550 V AC 250 V DC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 42.5 kA (380 V AC) 18 kA (415 V AC) 18 kA (440 V AC) 18 kA (480 V AC) 12.5 kA (500 V AC) 10 kA (250 V DC) 2 Poles in Series 18 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(240 V AC) 85 kA (380 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 36 kA (480 V AC) 25 kA (500 V AC) 20 kA (250 V DC) 2 Poles in Series 36 kA
Rated Uninterrupted Current (I_u)	400 A
Release	TMF
Release Type	TM

Short-Circuit Performance Level	N
Standards	IEC
Sub-type	A3
Terminal Connection Type	Front
Version	F

Certificados y Declaraciones (Número de Documento)

Ficha técnica, información técnica	1SDC210032D0204
Declaración de conformidad - CE	9AKK106713A5517
Environmental Information	1SDL000185R001
Instrucciones y manuales	1SDH000747R0001
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424

Clasificaciones

ETIM 4	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 5	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 6	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
Categoría RAEE	5. Small Equipment (No External Dimension More Than 50 cm)

Categorías

Productos y sistemas de baja tensión → Interruptores automáticos → Interruptores automáticos en caja moldeada → Formula DSA

