

PRODUCT-DETAILS

A3N 630 ELT-LI In=630 3p F F

A3N 630 ELT-LI In=630 3p F F



Información General

Tipo de producto extendido	A3N 630 ELT-LI In=630 3p F F
Código de producto	1SDA066566R1
EAN	8015644004781
Descripción corta	A3N 630 ELT-LI In=630 3p F F
Descripción larga	C.BREAKER FORMULA A3N 630 FIXED THREE-POLE WITH FRONT TERMINALS AND SOLID-STATE RELEASE IN AC ELT-LI R 630

Clasificación

EAN	8015644004781
Cantidad mínima de pedido	1 piece
Código arancelario	85362090

Dimensiones

Ancho del product	139.5 mm
Alto del producto	205 mm
Largo del product	103.5 mm
Peso del product	4.853 kg

Información de Embalaje

Embalaje Nivel 1 Unidades	1 piece
Embalaje Nivel 1 Ancho	286 mm
Embalaje Nivel 1 Alto	228 mm
Embalaje Nivel 1 Largo	244 mm
Embalaje Nivel 1 Peso	4.85 kg
Embalaje Nivel 1 EAN	8015644004781

Ambiente

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

Información Adicional

Electrical Durability	2000 cycle
Mechanical Durability	Nr. Operations 5000 cycle
Number of Poles	3
Opening Time	CB with SOR 15 ms CB with UVR ≤25 ms
Power Loss	at Rated Operating Conditions per Pole 41 W
Product Main Type	SACE FORMULA
Product Name	Moulded Case Circuit Breaker
Product Type	CB
Rated Current (I_n)	Main Circuit 630 A
Rated Impulse Withstand Voltage (U_{imp})	6 kV
Rated Insulation Voltage (U_i)	690 V
Rated Operational Voltage	550 V AC
Rated Service Short- Circuit Breaking Capacity (I_{cs})	(240 V AC) 42.5 kA (380 V AC) 18 kA (415 V AC) 18 kA (440 V AC) 18 kA (480 V AC) 12.5 kA (500 V AC) 10 kA
Rated Ultimate Short- Circuit Breaking Capacity (I_{cu})	(240 V AC) 85 kA (380 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 36 kA (480 V AC) 25 kA (500 V AC) 20 kA
Rated Uninterrupted Current (I_u)	630 A
Release	ELT LI
Release Type	EL
Short-Circuit Performance Level	N
Standards	IEC
Sub-type	A3

Terminal Connection Type	Front
Version	F

Certificados y Declaraciones (Número de Documento)

Ficha técnica, información técnica	1SDC210032D0204
Declaración de conformidad - CE	9AKK106713A5517
Environmental Information	1SDL000184R0001
Instrucciones y manuales	1SDH000747R0001
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424

Clasificaciones

ETIM 4	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 5	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 6	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
Categoría RAEE	5. Small Equipment (No External Dimension More Than 50 cm)

Categorías

Productos y sistemas de baja tensión → Interruptores automáticos → Interruptores automáticos en caja moldeada → Formula DSA

