
PRODUCT-DETAILS

XT2S 160 TMA 125-1250 3p F F

XT2S 160 TMA 125-1250 3p F F



Información General

| | |
|----------------------------|--|
| Tipo de producto extendido | XT2S 160 TMA 125-1250 3p F F |
| Código de producto | 1SDA067559R1 |
| EAN | 8015644014551 |
| Descripción corta | XT2S 160 TMA 125-1250 3p F F |
| Descripción larga | C.BREAKER TMAX XT2S 160 FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMA R 125 I3=625...1250 A |

Clasificación

| | |
|---------------------------|---------------|
| E-Number (Finland) | 3638053 |
| EAN | 8015644014551 |
| Cantidad mínima de pedido | 1 piece |
| Código arancelario | 85362090 |

Dimensiones

| | |
|-------------------|---------|
| Ancho del product | 90 mm |
| Alto del producto | 130 mm |
| Largo del product | 82.5 mm |

| | |
|------------------|----------|
| Peso del product | 1.572 kg |
|------------------|----------|

Información de Embalaje

| | |
|------------------------------|---------------|
| Embalaje Nivel 1 Unidades | 1 piece |
| Embalaje Nivel 1 Ancho | 130 mm |
| Embalaje Nivel 1 Alto | 208 mm |
| Embalaje Nivel 1 Largo | 145 mm |
| Embalaje Nivel 1 Peso | 1.655 kg |
| Embalaje Nivel 1 EAN | 8015644014551 |

Ambiente

| | |
|-------------|--|
| RoHS Status | Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019 |
|-------------|--|

Información Adicional

| | |
|---|--|
| Circuit Breaker Type to be Associated | Power Distribution |
| Current Type | AC/DC |
| Electrical Durability | 120 cycles per hour 8000 cycle |
| Mechanical Durability | Nr. Operations 240 cycles per hour Nr. Operations 25000 cycle |
| Number of Poles | 3 |
| Opening Time | CB with SOR 15 ms CB with UVR 15 ms |
| Order Multiple | 1 piece |
| Power Loss | at Rated Operating Conditions per Pole 11.4 W |
| Product Main Type | SACE Tmax XT |
| Product Name | Moulded Case Circuit Breaker |
| Product Type | CB |
| Rated Current (I_n) | 125 A |
| Rated Frequency (f) | 50 / 60 Hz |
| Rated Voltage (U_r) | 690 V |
| Rated Impulse Withstand Voltage (U_{imp}) | 8 kV |
| Rated Instantaneous Short-Circuit Current Setting (I_s) | 625...1250 A |
| Rated Insulation Voltage (U_i) | 1000 V |
| Rated Operational Voltage | 690 V AC 500 V DC |
| Rated Service Short-Circuit Breaking Capacity (I_{cs}) | (220 V AC) 85 kA (230 V AC) 85 kA (240 V AC) 85 kA (380 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA |

| | |
|---|--|
| | (500 V AC) 36 kA (525 V AC) 25 kA (690 V AC) 12 kA (250 V DC) 2 Poles in Series 50 kA (500 V DC) 3 Poles in Series 50 kA |
| Rated Ultimate Short-Circuit Breaking Capacity (I_{cu}) | (220 V AC) 85 kA (230 V AC) 85 kA (240 V AC) 85 kA (380 V AC) 50 kA (415 V AC) 50 kA (440 V AC) 50 kA (500 V AC) 36 kA (525 V AC) 25 kA (690 V AC) 12 kA (250 V DC) 2 Poles in Series 50 kA (500 V DC) 3 Poles in Series 50 kA |
| Rated Uninterrupted Current (I_u) | 160 A |
| Release | TMA |
| Release Type | TM |
| Setting Range | 87.5...125 A |
| Short-Circuit Performance Level | S |
| Standards | IEC |
| Sub-type | XT2 |
| Terminal Connection Type | Fixed Circuit-Breakers |
| Version | F |

Certificados y Declaraciones (Número de Documento)

| | |
|------------------------------------|------------------------------------|
| Ficha técnica, información técnica | 1SDC210100D0206 1SDC210099D0206 |
| Declaración de conformidad - CE | 9AKK106713A5901 |
| Environmental Information | 9AKK107991A8215 |
| GL Certificate | 1SDL000163R0093 |
| Instrucciones y manuales | 1SDH000721R0001 |
| LR Certificate | 1SDL000163R0100 |
| REACH Declaration | 9AKK108466A1425 |
| RoHS Information | 9AKK108466A1424 |

Clasificaciones

| | |
|----------------------------|--|
| ETIM 4 | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| ETIM 5 | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| ETIM 6 | EC000228 - Power circuit-breaker for trafo/generator/installation prot. |
| ETIM 7 | EC000228 - Power circuit-breaker for trafo/generator/installation protection |
| Object Classification Code | Q |
| UNSPSC | 39120000 |
| Categoría RAEE | 5. Small Equipment (No External Dimension More Than 50 cm) |

Categorías

Productos y sistemas de baja tensión → Interruptores automáticos → Interruptores automáticos en caja moldeada → Tmax XT

