

PRODUCT-DETAILS

A1N 125 TMF 32-400 3p F F

A1N 125 TMF 32-400 3p F F



Información General

Tipo de producto extendido	A1N 125 TMF 32-400 3p F F
Código de producto	1SDA068760R1
EAN	8015644030001
Descripción corta	A1N 125 TMF 32-400 3p F F
Descripción larga	C.BREAKER FORMULA A1N 125 FIXED THREE-POLE WITH FRONT TERMINALS AND THERMOMAGNETIC RELEASE TMF R 32-400 A

Clasificación

EAN	8015644030001
Cantidad mínima de pedido	1 piece
Código arancelario	85362090
Order Code US and Canada	AAN032TW

Dimensiones

Ancho del product	76.2 mm
Alto del producto	130 mm
Largo del product	60 mm
Peso del product	0.75 kg

Información de Embalaje

Embalaje Nivel 1 Unidades	1 piece
Embalaje Nivel 1 Ancho	136.5 mm
Embalaje Nivel 1 Alto	124 mm
Embalaje Nivel 1 Largo	110.5 mm
Embalaje Nivel 1 Peso	0.8 kg
Embalaje Nivel 1 EAN	8015644030001

Ambiente

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

Información Adicional

Electrical Durability	1500 cycle
Mechanical Durability	Nr. Operations 8500 cycle
Number of Poles	3
Opening Time	CB with SOR 15 ms CB with UVR 15 ms
Power Loss	at Rated Operating Conditions per Pole 4 W
Product Main Type	SACE FORMULA
Product Name	Moulded Case Circuit Breaker
Product Type	CB
Rated Current (I_n)	Main Circuit 32 A
Rated Impulse Withstand Voltage (U_{imp})	6 kV
Rated Insulation Voltage (U_i)	690 V
Rated Operational Voltage	550 V AC 250 V DC
Rated Service Short-Circuit Breaking Capacity (I_{cs})	(240 V AC) 25 kA (380 V AC) 18 kA (415 V AC) 9 kA (440 V AC) 6.25 kA (480 V AC) 4.5 kA (500 V AC) 2.5 kA (250 V DC) 2 Poles in Series 5 kA
Rated Ultimate Short-Circuit Breaking Capacity (I_{cu})	(240 V AC) 100 kA (380 V AC) 36 kA (415 V AC) 36 kA (440 V AC) 25 kA (480 V AC) 18 kA (500 V AC) 10 kA (250 V DC) 10 kA
Rated Uninterrupted Current (I_u)	125 A
Release	TMF
Release Type	TM
Short-Circuit Performance Level	N
Standards	IEC
Sub-type	A1
Terminal Connection Type	Front
Version	F

Certificados y Declaraciones (Número de Documento)

Ficha técnica, información técnica	1SDC210032D0204
Declaración de conformidad - CE	9AKK106713A5519
Environmental Information	1SDL000183R0001
Instrucciones y manuales	1SDH000717R0001
REACH Declaration	9AKK108466A1425
RoHS Information	9AKK108466A1424

Clasificaciones

ETIM 4	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 5	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 6	EC000228 - Power circuit-breaker for trafo/generator/installation prot.
ETIM 7	EC000228 - Power circuit-breaker for trafo/generator/installation protection
Object Classification Code	Q
Categoría RAEE	5. Small Equipment (No External Dimension More Than 50 cm)

Categorías

Productos y sistemas de baja tensión → Interruptores automáticos → Interruptores automáticos en caja moldeada → Formula DSA

