

PRODUCT-DETAILS

UA110-30-00RA-84

UA110-30-00RA 110V 50Hz Contactor



Información General

Tipo de producto extendido	UA110-30-00RA-84
Código de producto	1SFL451024R8400
EAN	7320500260555
Descripción corta	UA110-30-00RA 110V 50Hz Contactor
Descripción larga	A 3-phase Contactor suitable for Capacitor switching application. Maximum permissible peak current 100 times the nominal RMS current. Operated with a control voltage, versions from 24V to 690 V

Clasificación

Cantidad mínima de pedido	1 piece
Código arancelario	85364900

Descargas Populares

Ficha técnica, información técnica	1SBC101145L0202
Instrucciones y manuales	5309660-60

Dimensiones

Ancho del product	90 mm
Largo del product	155.6 mm
Alto del producto	170 mm
Peso del product	1.8 kg

Technical

Number of Main Contacts NO	3
Number of Main Contacts NC	0
Number of Auxiliary Contacts NO	0
Number of Auxiliary Contacts NC	0
Rated Operational Voltage	Main Circuit 1000 V
Rated Frequency (f)	Main Circuit 50 Hz
Conventional Free-air Thermal Current (I_{th})	acc. to IEC 60947-4-1, Open Contactors $q = 40^\circ\text{C}$ 160 A
Rated Operational Current AC-1 (I_e)	(690 V) 40°C 160 A (690 V) 55°C 145 A (690 V) 60°C 145 A (690 V) 70°C 130 A
Rated Operational Current AC-3 (I_e)	(415 V) 55°C 110 A (440 V) 55°C 100 A (500 V) 55°C 100 A (690 V) 55°C 82 A (1000 V) 55°C 30 A (380 / 400 V) 55°C 110 A (220 / 230 / 240 V) 55°C 110
Rated Operational Power AC-6b (P_e)	(230 / 240 V) 40°C , 50 / 60 Hz 45 kvar (230 / 240 V) 55°C , 50 / 60 Hz 40 kvar (230 / 240 V) 70°C , 50 / 60 Hz 35 kvar (400 / 415 V) 40°C , 50 / 60 Hz 80 kvar (400 / 415 V) 70°C , 50 / 60 Hz 60 kvar (400 / 415 V) 55°C , 50 / 60 Hz 70 kvar (440 V) 40°C , 50 / 60 Hz 85 kvar (440 V) 55°C , 50 / 60 Hz 75 kvar (440 V) 70°C , 50 / 60 Hz 70 kvar (500 / 550 V), 40°C , 50 / 60 Hz 95 kvar (500 / 550 V) 55°C , 50 / 60 Hz 82 kvar (500 / 550 V) 70°C , 50 / 60 Hz 78 kvar (690 V) 40°C , 50 / 60 Hz 130 kvar (690 V) 55°C , 50 / 60 Hz 110 kvar (690 V) 70°C , 50 / 60 Hz 100 kvar
Rated Breaking Capacity AC-3	8 x I_e AC-3
Rated Making Capacity AC-3	10 x I_e AC-3
Maximum Breaking Capacity	$\cos \phi = 0.45$ ($\cos \phi = 0.35$ for $I_e > 100$ A) at 440 V 1160 A $\cos \phi = 0.45$ ($\cos \phi = 0.35$ for $I_e > 100$ A) at 690 V 800 A
Maximum Electrical Switching Frequency	(AC-1) 300 cycles per hour (AC-2 / AC-4) 150 cycles per hour (AC-3) 300 cycles per hour
Rated Insulation Voltage (U_i)	acc. to IEC 60947-4-1 and VDE 0110 (Gr. C) 1000 V acc. to UL/CSA 600 V
Rated Impulse Withstand	Main Circuit 8 kV

Voltage (U _{imp})	
Mechanical Durability	10 million
Maximum Mechanical Switching Frequency	3600 cycles per hour
Coil Operating Limits	(acc. to IEC 60947-4-1) 0.85 x U _c Min. ... 1.1 x U _c Max. (at θ ≤ 70 °C)
Rated Control Circuit Voltage (U _c)	50 Hz 110 V 60 Hz 110 ... 120 V
Coil Consumption	Holding at Max. Rated Control Circuit Voltage 50 Hz 22 V·A Holding at Max. Rated Control Circuit Voltage 60 Hz 26 V·A Pull-in at Max. Rated Control Circuit Voltage 50 Hz 350 V·A Pull-in at Max. Rated Control Circuit Voltage 60 Hz 450 V·A
Operate Time	Between Coil De-energization and NC Contact Closing 7 ... 15 ms Between Coil Energization and NO Contact Closing 10 ... 25 ms
Connecting Capacity Main Circuit	Bar 30 mm ² Flexible with Cable End 2 x 6 ... 35 mm ² Rigid 1 x 10 ... 95 mm ²
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 2x 0.75 ... 2.5 mm ² Flexible with Insulated Ferrule 2x 0.75 ... 2.5 mm ² Flexible 2x0.75 ... 2.5 mm ² Solid 2 x 1 ... 4 mm ² Stranded 2 x 1 ... 4 mm ²
Grado de protección	acc. to IEC 60529, IEC 60947-1, EN 60529 Coil Terminals IP20 acc. to IEC 60529, IEC 60947-1, EN 60529 Main Terminals IP10
Connecting Terminals (delivered in open position) Main Poles	M8 hexagon socket screw with single connector
Terminal Type	Cable Clamp

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Main Circuit 600 V
----------------------------------	--------------------

Ambiente

Temperatura ambiente	Close to Contactor Fitted with Thermal O/L Relay (0.85 ... 1.1 U _c) -25 ... 50 °C Close to Contactor without Thermal O/L Relay (0.85 ... 1.1 U _c) -40 ... 70 °C Close to Contactor for Storage -60 ... +80 °C
Maximum Operating Altitude Permissible	Without Derating 3000 m
Resistance to Shock acc. to IEC 60068-2-27	Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: A 20 g Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock Direction: A 20 g Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock Direction: B1 15 g Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock Direction: C1 20 g Half-sine Pulse for 11 ms, No Change in Contact Position, Closed, Shock Direction: C2 20 g Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: B1 5 g Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: B2 15 g Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: C1 20 g Half-sine Pulse for 11 ms, No Change in Contact Position, Open, Shock Direction: C2 20 g

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

Certificados y Declaraciones (Número de Documento)

CB Certificate	SE-72477
cULus Certificate	20160916- E36588
Declaración de conformidad - CE	2CMT2015-005436
Environmental Information	1SFC101001D0201
Instrucciones y manuales	5309660-60
RoHS Information	2CMT2015-005436

Información de Embalaje

Embalaje Nivel 1 Unidades	box 1 piece
Embalaje Nivel 1 Ancho	170 mm
Embalaje Nivel 1 Largo	140 mm
Embalaje Nivel 1 Alto	170 mm
Embalaje Nivel 1 Peso	2 kg
Embalaje Nivel 1 EAN	7320500260555

Clasificaciones

Object Classification Code	Q
ETIM 4	EC001079 - Capacitor magnet contactor
ETIM 5	EC001079 - Capacitor magnet contactor
ETIM 6	EC001079 - Capacitor contactor
ETIM 7	EC001079 - Capacitor contactor
eClass	V11.0 : 27371006
UNSPSC	39121529
IDEA Granular Category Code (IGCC)	4756 >> Capacitor magnet contactor

Categorías

Productos y sistemas de baja tensión → Aparatos de control → Contactores → Contactores → UA and UA..RA Contactors

