

PRODUCT-DETAILS

CR-M012DC4

CR-M012DC4 Pluggable interface relay 4c/o,
A1-A2=12VDC, 250V/6A



Información General

Tipo de producto extendido	CR-M012DC4
Código de producto	1SVR405613R4000
EAN	4013614497773
Descripción corta	CR-M012DC4 Pluggable interface relay 4c/o, A1-A2=12VDC, 250V/6A
Descripción larga	The CR-M012DC4 pluggable interface relay is from the CR-M (miniature) relay range. This relay operates with a 12 V DC rated control supply voltage and has a 4 c/o (SPDT) output with contacts rated at 250 V / 6 A. The relay has an integrated blue test button for manual actuation and locking of the output contacts. Standard sockets, logic sockets, pluggable function modules, holder and marker are available as accessories.

Clasificación

Cantidad mínima de pedido	10 piece
Código arancelario	85364900

Descargas Populares

Ficha técnica, información técnica	2CDC110004C0210_05
Instrucciones y manuales	1SVC405600M9000

Dimensiones

Ancho del product	21.2 mm
Alto del producto	35.6 mm
Largo del product	27.5 mm
Peso del product	0.033 kg

Technical

Function	Pluggable miniature interface relay CR-M
Sub-Function	Relay w/o built in LED
Output	4 c/o (SPDT) contacts
Output Signal	250 V / 6 A
Rated Control Supply Voltage (U _s)	12 V DC
Terminal Type	Flat-Pin Connections

Ambiente

Temperatura ambiente	Funcionamiento -40 ... +70 °C Almacenamiento -40 ... +85 °C
Maximum Operating Altitude Permissible	Without Derating 2000 m
RoHS Status	Following EU Directive 2011/65/EU

Technical UL/CSA

Maximum Operating Voltage UL/CSA	300 V AC
Ampere Rating UL/CSA	2.5 A
Pilot Duty UL/CSA	B300

Certificados y Declaraciones (Número de Documento)

CCC Certificate	CCC_2014010303720193
CQC Certificate	CQC2014010303720193
CSA Certificate	CSA_2735700
cUR Certificate	cUR_E244330
Declaration of Conformity - CCC	2020980303000200
Declaración de conformidad - CE	1SVD982021-0003
Declaration of Conformity - UKCA	1SVD982021-1000
EAC Certificate	EAC_RU_C-DE.ME77.B.00446-19
Environmental Information	1SAA981009-2401
Instrucciones y manuales	1SVC405600M9000
LR Certificate	LR_05_20002_E5
RMRS Certificate	RMRS_1740019250
RoHS Information	1SVD982021-0003
UR Certificate	UR_E244330
VDE Certificate	VDE_40040327

Información de Embalaje

Embalaje Nivel 1 Unidades	box 10 piece
---------------------------	--------------

Embalaje Nivel 1 Ancho	114 mm
Embalaje Nivel 1 Alto	61 mm
Embalaje Nivel 1 Largo	50 mm
Embalaje Nivel 1 Peso	0.35 kg
Embalaje Nivel 1 EAN	4013614373480

Clasificaciones

Object Classification Code	K
ETIM 4	EC001437 - Switching relay
ETIM 5	EC001437 - Switching relay
ETIM 6	EC001437 - Switching relay
ETIM 7	EC001437 - Switching relay
eClass	V11.0 : 27371601
UNSPSC	39122331
E-Number (Finland)	2712646

Categorías

Productos y sistemas de baja tensión → Aparatos de control → Relés electrónicos → Relés de interface

