

PRODUCT-DETAILS

CR-U024DC2

CR-U024DC2 Pluggable interface relay 2c/o, A1-A2=24VDC, 250V/10A



Información General

Tipo de producto extendido	CR-U024DC2
Código de producto	1SVR405621R1000
EAN	4013614498374
Descripción corta	CR-U024DC2 Pluggable interface relay 2c/o, A1-A2=24VDC, 250V/10A
Descripción larga	The CR-U024DC2 pluggable interface relay is from the CR-U (universal) relay range. This relay operates with a 24 V DC rated control supply voltage and has 2 c/o (SPDT) output contacts rated at 250 V / 10 A. The relay has an integrated blue test button for manual actuation and locking of the output contacts. Standard sockets, pluggable function modules, holder and marker are available as accessories.

Clasificación

Cantidad mínima de pedido	10 piece
Código arancelario	85364900

Descargas Populares

Ficha técnica, información técnica	2CDC110004C0210_05
Instrucciones y manuales	1SVC405600M9000

Dimensiones

Ancho del product	35 mm
Alto del producto	54.4 mm
Largo del product	35 mm
Peso del product	0.083 kg

Technical

Function	Pluggable universal interface relay CR-U
Sub-Function	Relay w/o built in LED
Output	2 c/o (SPDT) contacts
Output Signal	250 V / 10 A
Rated Control Supply Voltage (U _s)	24 V DC
Terminal Type	Pin

Ambiente

Temperatura ambiente	Funcionamiento -40 ... +70 °C Almacenamiento -40 ... +85 °C
Maximum Operating Altitude Permissible	Without Derating 2000 m
RoHS Status	Following EU Directive 2011/65/EU

Technical UL/CSA

Maximum Operating Voltage UL/CSA	300 V AC
Ampere Rating UL/CSA	5 A
Pilot Duty UL/CSA	B300

Certificados y Declaraciones (Número de Documento)

CCC Certificate	CCC_2017010303949759
CQC Certificate	CQC2017010303949759
CSA Certificate	CSA_1587291
Declaration of Conformity - CCC	2020980303000199
Declaración de conformidad - CE	1SVD982021-0003
Declaration of Conformity - UKCA	1SVD982021-1000
EAC Certificate	EAC_RU_C-DE.ME77.B.00446-19
Environmental Information	1SAA981009-2401
Instrucciones y manuales	1SVC405600M9000
LR Certificate	LR_05_20002_E5
RMRS Certificate	RMRS_1740019250
RoHS Information	1SVD982021-0003
UR Certificate	UR_E244330
VDE Certificate	VDE_40019116

Información de Embalaje

Embalaje Nivel 1 Unidades	box 10 piece
Embalaje Nivel 1 Ancho	182 mm

Embalaje Nivel 1 Alto	76 mm
Embalaje Nivel 1 Largo	77 mm
Embalaje Nivel 1 Peso	0.87 kg
Embalaje Nivel 1 EAN	4013614374012

Clasificaciones

Object Classification Code	K
ETIM 4	EC001437 - Switching relay
ETIM 5	EC001437 - Switching relay
ETIM 6	EC001437 - Switching relay
ETIM 7	EC001437 - Switching relay
eClass	V11.0 : 27371601
UNSPSC	39122331
E-Number (Finland)	2712767
E-Number (Sweden)	4005412

Categorías

Productos y sistemas de baja tensión → Aparatos de control → Relés electrónicos → Relés de interface

