

PRODUCT-DETAILS

CM-PFE.2

CM-PFE.2 Phase sequence monitoring relay 1c/o, L1-L2-L3=200-500VAC



General Information

Extended Product Type	CM-PFE.2
Product ID	1SVR550826R9100
EAN	4013614501814
Catalog Description	CM-PFE.2 Phase sequence monitoring relay 1c/o, L1-L2-L3=200-500VAC
Long Description	The CM-PFE.2 relay is from the CM three-phase monitors range. This relay operates with a rated control supply voltage / three-phase measuring voltage of 200-500 V AC and has a 1 c/o output (closed circuit principle) with contacts rated at 250 V / 4 A. The CM-PFE.2 monitors the phase loss and phase sequence. The corresponding threshold values are fixed. The relay is suitable for monitoring of three phase mains.

Ordering

Minimum Order Quantity	1 piece
Customs Tariff Number	85364900

Popular Downloads

Data Sheet, Technical Information	2CDC112231D0201
Instructions and Manuals	1SVC550510M0001

Dimensions

Product Net Width	22.5 mm
Product Net Depth / Length	78.5 mm
Product Net Height	78 mm
Product Net Weight	0.067 kg

Technical

Function	Phase failure detection Phase sequence monitoring
Standards	CAN/CSA C22.2 No.14 IEC/EN 63000 IEC/EN 60255-27 IEC/EN 61000-6-2 IEC/EN 61000-6-3 UL 508
Measuring Range	(L-L) 200 ... 500 V AC
Rated Control Supply Voltage (U _s)	(L-L) 200 ... 500 V AC
Rated Frequency (f)	Supply Circuit 50/60 Hz
Output	1 c/o (SPDT) contact
Time Range	500 ms start-up delay 500 ms tripping delay
Terminal Type	Screw Terminals
Rated Operational Current AC-12 (I _e)	(230 V) 4 A
Rated Operational Current AC-15 (I _e)	(230 V) 3 A
Rated Operational Current DC-12 (I _e)	(24 V) 4 A
Rated Operational Current DC-13 (I _e)	(24 V) 2 A
Rated Insulation Voltage (U _i)	Input Circuit / Output Circuit 600 V
Rated Impulse Withstand Voltage (U _{imp})	Input Circuit 6 kV
Degree of Protection	Housing IP50 Terminals IP20
Overvoltage Category	III
Pollution Degree	3
Short-Circuit Protective Devices	Output Circuit NC - F Type Fuses 6 A Output Circuit NO - F Type Fuses 10 A
Connecting Capacity	Flexible with Ferrule 2x 0.75 ... 1.5 mm ² Flexible 2x 1 ... 1.5 mm ² Rigid 2x 0.75 ... 1.5 mm ²
Tightening Torque	0.6 ... 0.8 N·m
Wire Stripping Length	10 mm
Mounting Position	1 ... 6
Mounting on DIN Rail	TH35-15 (35 x 15 mm Mounting Rail) acc. to IEC 60715 TH35-7.5 (35 x 7.5 mm Mounting Rail) acc. to IEC 60715

Environmental

Ambient Air Temperature	Operation -20 ... +60 °C Storage -40 ... +85 °C
Maximum Operating Altitude Permissible	Without Derating 2000 m
RoHS Status	Following EU Directive 2011/65/EU

Technical UL/CSA

Maximum Operating Voltage UL/CSA	Output Circuit 250 V AC
Contact Rating UL/CSA	B300
Connecting Capacity UL/CSA	Flexible with Ferrule 2x 18-16 AWG Flexible 2x 18-16 AWG Rigid 2x 18-16 AWG
Tightening Torque UL/CSA	7.08 in-lb

Certificates and Declarations (Document Number)

CCC Certificate	CCC_2013010303605960
CQC Certificate	CQC2013010303605960
cUL Certificate	cUL508_E140448
Declaration of Conformity - CCC	2020980303000202
Declaration of Conformity - CE	1SVD981026-00
Declaration of Conformity - UKCA	1SVD981026-10
EAC Certificate	EAC_RU_C-DE.ME77.B.03206
Instructions and Manuals	1SVC550510M0001
RoHS Information	1SVD981026-00
UL Certificate	UL508_E140448

Container Information

Package Level 1 Units	box 1 piece
Package Level 1 Width	24 mm
Package Level 1 Height	83 mm
Package Level 1 Depth / Length	25 mm
Package Level 1 Gross Weight	0.078 kg
Package Level 1 EAN	4013614501814

Classifications

Object Classification Code	B
ETIM 5	EC001441 - Phase monitoring relay
ETIM 6	EC001441 - Phase monitoring relay
ETIM 7	EC001441 - Phase monitoring relay
eClass	V11.0 : 27371803
UNSPSC	39121536

Categories

Low Voltage Products and Systems → Control Products → Electronic Relays and Controls → Three Phase Monitors

