

PRODUCT-DETAILS

# ACS150-03E-06A7-2

## ACS150-03E-06A7-2 Pn 1,1kW, I2n 6,7A IP20



### Información General

Global Commercial Alias	ACS150-03E-06A7-2
Código de producto	68582032
ABB Type Designation	ACS150-03E-06A7-2
EAN	6410038079390
Descripción corta	ACS150-03E-06A7-2 Pn 1,1kW, I2n 6,7A IP20
Descripción larga	The ACS150 drives are designed to be incorporated into a wide variety of machines such as mixers, conveyors, fans or pumps. The ACS150 drives have an integrated user panel, potentiometer and a variety of features such as pre-defined connection macros, making drive selection and configuration easy. With an optional FlashDrop tool these drives can be configured quickly in volume.

### Clasificación

Country of Origin	China (CN)
Código arancelario	85044084
Invoice Description	ACS150-03E-06A7-2 Pn 1,1kW, I2n 6,7A IP20
Made To Order	No
Cantidad mínima de pedido	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

### Dimensiones

Peso del product	1.4 kg
Largo del product	142 mm
Alto del producto	239 mm
Product Net Length	142 mm
Ancho del product	70 mm
Embalaje Nivel 1 Largo	345 mm
Embalaje Nivel 1 Alto	130 mm
Embalaje Nivel 1 Ancho	215 mm
Embalaje Nivel 1	1 carton
Unidades	

## Technical

Number of Phases	3
Grado de protección	IP20
Enclosure Type NEMA	Open Type
Frequency (f)	50/60 Hz
Input Voltage (U <sub>in</sub> )	200 ... 240 V
Mounting Type	Module for cabinet building
Number of Hardware Interfaces	Industrial Ethernet 0 PROFINET 0 RS-232 0 RS-422 0 RS-485 0 Serial TTY 0 USB 0 Parallel 0 Other 1
Includes	With control unit Without optical interface With PC connection
Analog Inputs	1
Analog Outputs	0
Number of Digital In/Outputs	5/0
Output Current, Light-Overload Use	6.7 A
Output Current, Normal Use	6.7 A
Output Power, Light-Overload Use	1.1 kW
Output Power, Normal Use	1.1 kW
Apparent Power Output	2.7 kV·A
Efficiency Level	IE2
Standby Loss	11 W
Complete Drive Module Efficiency (61800-9-2)	

Operating Point Frequency / Current	Absolute Loss	Relative Loss	Efficiency
0 / 25 %	37 W	1.4 %	79.2 %
0 / 50 %	43 W	1.6 %	86.3 %
0 / 100 %	59 W	2.2 %	89.6 %
50 / 25 %	39 W	1.5 %	88.3 %
50 / 50 %	47 W	1.8 %	92.4 %
50 / 100 %	66 W	2.5 %	94.1 %
90 / 50 %	52 W	1.9 %	95.2 %
90 / 100 %	75 W	2.8 %	96.2 %

Temperature Rating

Maximum 40 °C

---

**Información Adicional**

---

Product Main Type	ACS150
Product Name	Frequency converter

---

---

**Clasificaciones**

---

Product Series	ACS150
ETIM 7	EC001857 - Frequency converter =< 1 kV
UNSPSC	39122001

---

---

**Ambiente**

---

SCIP	bc1ce83c-5b27-4060-9b9d-c7a3b0020c1e Finland (FI)
Categoría RAEE	5. Small Equipment (No External Dimension More Than 50 cm)

---

---

**Categorías**

---

Convertidores de frecuencia → Convertidores de frecuencia de baja tensión de CA → Microconvertidores de frecuencia → ACS150 - Micro Drive

