

PRODUCT-DETAILS

# CAF6-11M

## CAF6-11M Auxiliary Contact



### Información General

Tipo de producto extendido	CAF6-11M
Código de producto	GJL1201330R0003
EAN	4013614142659
Descripción corta	CAF6-11M Auxiliary Contact
Descripción larga	The CAF6-11M is an auxiliary contact for front mounting with 2 auxiliary contact and screw terminals.

### Clasificación

Cantidad mínima de pedido	1 piece
Código arancelario	85365080

### Descargas Populares

Ficha técnica, información técnica	1SBC100214C0202
Instrucciones y manuales	2CDC102005M0101
Instructions and Manuals (Part 2)	2CDC102005M0101
Dimension Diagram	GJL1200446F0001

## Dimensiones

Ancho del product	47.5 mm
Alto del producto	29 mm
Largo del product	26.5 mm
Peso del product	0.02 kg

## Technical

Rated Operational Voltage	Auxiliary Circuit 690 V AC Auxiliary Circuit 250 V DC
Rated Frequency (f)	Auxiliary Circuit 50 Hz Auxiliary Circuit 60 Hz Auxiliary Circuit DC
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	Auxiliary Circuit 6 kV
Rated Insulation Voltage (U <sub>i</sub> )	690 V
Number of Poles	2
Grado de protección	IP20
Connecting Capacity Auxiliary Circuit	Flexible with Ferrule 1/2x 1 ... 2.5 mm <sup>2</sup> Flexible 1/2x 1 ... 2.5 mm <sup>2</sup> Rigid 1/2x 1 ... 4 mm <sup>2</sup>
Tightening Torque	Auxiliary Circuit 0.8 ... 1.1 N·m
Wire Stripping Length	Auxiliary Circuit 9 mm
Standards	IEC/EN 60947-1 IEC/EN 60947-4-1 IEC/EN 60947-5-1 UL 60947-1 UL 60947-4-1
Number of Auxiliary Contacts NO	1
Number of Auxiliary Contacts NC	1
Number of Main Contacts NC	0
Number of Main Contacts NO	0
Conventional Free-air Thermal Current (I <sub>th</sub> )	Auxiliary Circuit 6 A
Product Name	Auxiliary Contact
Suitable For	B6-30-10 BC6-30-10 B7-30-10 BC7-30-10 VB6-30-10 VBC6-30-10 VB7-30-10 VBC7-30-10 VB6A-30-10 VBC6A-30-10 VB7A-30-10 VBC7A-30-10
Suitable for Product Class	Mini Contactors

## Technical UL/CSA

Maximum Operating Voltage UL/CSA	600 V AC
Connecting Capacity Auxiliary Circuit UL/CSA	Stranded 1/2x 22-10 AWG
Tightening Torque	Auxiliary Circuit 7 in·lb

UL/CSA

Contact Rating UL/CSA

A600

## Ambiente

Temperatura ambiente	Funcionamiento -25 ... +55 °C Almacenamiento -40 ... +80 °C
Maximum Operating Altitude Permissible	2000 m
Resistance to Shock acc. to IEC 60068-2-27	11 ms Pulse 15g
Resistance to Vibrations acc. to IEC 60068-2-6	5g / 5 ... 150 Hz
RoHS Status	Following EU Directive 2011/65/EU

## Certificados y Declaraciones (Número de Documento)

CQC Certificate	CQC2003010304064035
cULus Certificate	cUL_E48139
Declaration of Conformity - CCC	2020980304001309
Declaración de conformidad - CE	1SAD938517-0001
Declaration of Conformity - UKCA	1SAD938501-1001
EAC Certificate	1SAA938002-2701
Instrucciones y manuales	2CDC102005M0101
Instructions and Manuals (Part 2)	2CDC102005M0101
RMRS Certificate	1SAA938001-0704
RoHS Information	1SAD938517-0001
UL Certificate	UL_E48139

## Información de Embalaje

Embalaje Nivel 1 Ancho	115 mm
Embalaje Nivel 1 Largo	280 mm
Embalaje Nivel 1 Alto	54 mm
Embalaje Nivel 1 Peso	0.24 kg
Embalaje Nivel 1 EAN	4013614412240
Embalaje Nivel 1 Unidades	10 piece

## Clasificaciones

Object Classification Code	K
ETIM 4	EC000041 - Auxiliary contact block
ETIM 5	EC000041 - Auxiliary contact block
ETIM 6	EC000041 - Auxiliary contact block
ETIM 7	EC000041 - Auxiliary contact block
eClass	V11.0 : 27371302
UNSPSC	39121522
E-Number (Finland)	3709108

---

## Categorías

---

Productos y sistemas de baja tensión → Aparatos de control → Contactores → Mini Contactors Accessories

