

PRODUCT-DETAILS

MLBL-01G

MLBL-01G LED block



Información General

Tipo de producto extendido	MLBL-01G
Código de producto	1SFA611621R1012
EAN	7320500544570
Descripción corta	MLBL-01G LED block
Descripción larga	Modular LED block - 24V AC / DC, integrated LED - Green - Illuminated

Clasificación

Cantidad mínima de pedido	10 piece
Código arancelario	85369001

Descargas Populares

Ficha técnica, información técnica	1SFC151007C02__
Instrucciones y manuales	1SFC151011M0201

Dimensiones

Ancho del product	0.01 m
Alto del producto	0.044 m

Largo del product	0.042 m
Peso del product	0.01 kg

Technical

Temperatura ambiente	Funcionamiento -25 ... +70 °C Almacenamiento -40 ... +85 °C
Color	Green
Illumination	Illuminated
Lamp Type	24V AC / DC, integrated LED
Mounting Type	Front mounting
Grado de protección	Terminals IP20
Rated Frequency (f)	50 / 60 Hz
Rated Operational Voltage	24 V AC/DC
Power Loss	Approximately 0.3 W
Connecting Capacity	Flexible with Ferrule 1 x 0.75...2.5 mm ² Flexible with Ferrule 2 x 0.75...2.5 mm ² Flexible with Insulated Ferrule 1 x 0.75...2.5 mm ² Flexible with Insulated Ferrule 2 x 0.75...2.5 mm ² Flexible 1 x 0.75 ... 2.5 mm ² Flexible 2 x 0.75 ... 2.5 mm ² Solid 1 x 0.75...2.5 mm ² Solid 2 x 0.75...2.5 mm ²
Connecting Capacity Supply Circuit	Flexible with Ferrule 1x0.75...2.5 mm ² Flexible with Ferrule 2x0.75...2.5 mm ² Flexible with Insulated Ferrule 1x0.75...2.5 mm ² Flexible with Insulated Ferrule 2x0.75...2.5 mm ² Flexible 1x0.75...2.5 2 square millimeters Flexible 2x0.75...2.5 2 square millimeters
Connection Type	Screw Clamp
Terminal Type	Screw Terminals
Tightening Torque	0.9 N·m
Wire Stripping Length	8 mm
Suitable For	MCBH-00 MCBH5-00 MP1 MP2 MP3 MP4 MPMT3 MPMP3 M2SS1 M2SS2 M2SS3 M2SS4 M2SS5 M2SS6 M3SS1 M3SS2 M3SS3 M3SS4 M3SS5 M3SS6 M3SS7 M3SS8 MPM1
Suitable for Product Class	Pilot Devices

Technical UL/CSA

Connecting Capacity	1x 18...14 AWG
UL/CSA	2x 18...14 AWG

Ambiente

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	0635 4
RoHS Information	2CMT2015-005452
Categoría RAEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business

Certificados y Declaraciones (Número de Documento)

CB Certificate	SEMKO_SE-56219
CQC Certificate	CQC2008010305274953
cULus Certificate	9AKK107046A9925
Declaration of Conformity - CCC	2020980305001106
Declaración de conformidad - CE	2CMT2015-005452
DNV GL Certificate	E-14107
EAC Certificate	1SFC150017D1101
Environmental Information	1SAC200078H0001
Instrucciones y manuales	1SFC151011M0201
RoHS Information	2CMT2015-005452

Información de Embalaje

Embalaje Nivel 1 Unidades	bag 10 piece
Embalaje Nivel 1 Ancho	0.11 m
Embalaje Nivel 1 Largo	0.01 m
Embalaje Nivel 1 Alto	0.015 m
Embalaje Nivel 1 Peso	0.11 kg
Embalaje Nivel 1 EAN	7320500373002

Clasificaciones

Object Classification Code	E
ETIM 4	EC002024 - Accessories for control circuit devices
ETIM 5	EC000204 - Lamp holder block for control circuit devices
ETIM 6	EC000204 - Lamp holder block for control circuit devices
ETIM 7	EC000204 - Lamp holder block for control circuit devices
eClass	V11.0 : 27371209
UNSPSC	39121500
E-Number (Finland)	2315746
E-Number (Norway)	4373119
E-Number (Sweden)	3705055

Categorías

Productos y sistemas de baja tensión → Aparatos de control → Pulsantera → Accessories

Productos y sistemas de baja tensión → Aparatos de control → Pulsantera → Pilotos de señalización y operación

