

PRODUCT-DETAILS

# C2SS2-10B-11

## SELECTOR SWITCH C2SS2-10B-11



### Información General

Tipo de producto extendido	C2SS2-10B-11
Código de producto	1SFA619201R1076
EAN	7320500554944
Descripción corta	SELECTOR SWITCH C2SS2-10B-11
Descripción larga	Compact Selector Switch - 2-pos Fixed A&C - Short handle - Black - Non-illuminated - Black plastic - 1NO+1NC

### Clasificación

Cantidad mínima de pedido	10 piece
Código arancelario	8536501999

### Descargas Populares

Ficha técnica, información técnica	1SFC151007C02_
Instrucciones y manuales	1SFC151011M0201

### Dimensiones

Ancho del product	0.03 m
Alto del producto	0.03 m

Largo del product	0.072 m
Peso del product	0.024 kg

## Technical

Temperatura ambiente	Funcionamiento -25 ... +70 °C Almacenamiento -40 ... +85 °C
Color	Black
Actuator Type	Short handle
Bezel Material	Black Plastic
Illumination	Non-illuminated
Function	Maintained
Sub-Function	2-position
Maintained Positions	A, C
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	1
Grado de protección	Front IP66 Front IP67 Front IP69K Terminals IP20
Enclosure Type NEMA	Type1 Type12 Type13 Type3R Type4 Type4X
Pollution Degree	3
Rated Insulation Voltage (U <sub>i</sub> )	300 V
Rated Impulse Withstand Voltage (U <sub>imp</sub> )	6 kV
Rated Frequency (f)	50 / 60 Hz
Rated Operational Voltage	24 ... 300 V Maximum 300 V AC/DC
Rated Operational Current DC-13 (I <sub>e</sub> )	(24 V) 0.3 A (125 V) 0.2 A
Rated Operational Current AC-15 (I <sub>e</sub> )	(240 V) 1 A
Power Loss	Maximum 5 W
Mechanical Durability	0.5 million
Connecting Capacity	Flexible with Ferrule 1 x 0.5...1.5 mm <sup>2</sup> Flexible with Ferrule 2 x 0.5...1.5 mm <sup>2</sup> Flexible with Insulated Ferrule 1 x 0.5...1.5 mm <sup>2</sup> Flexible with Insulated Ferrule 2 x 0.5...1.5 mm <sup>2</sup> Flexible 1 x 0.5 ...1.5 mm <sup>2</sup> Flexible 2 x 0.5 ...1.5 mm <sup>2</sup> Solid 1 x 0.5...1.5 mm <sup>2</sup> Solid 2 x 0.5...1.5 mm <sup>2</sup>
Terminal Type	Screw Terminals
Tightening Torque	0.8 N·m
Wire Stripping Length	6 mm

## Technical UL/CSA

Connecting Capacity	1x 22...14 AWG
UL/CSA	2x 22...14 AWG

## Ambiente

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Date	0626 5
RoHS Information	2CMT2015-005451
Categoría RAEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business

### Certificados y Declaraciones (Número de Documento)

CB Certificate	CQC_CN_CN50749
CCC Certificate	2003010305054693_
CQC Certificate	CQC2003010305054693
cURus Certificate	UL_E496500-20171020
Declaration of Conformity - CCC	2020980305001187
Declaración de conformidad - CE	2CMT2015-005451
DNV GL Certificate	9AKK107046A3749
EAC Certificate	RU C-CN.ME77.B.00587/20
Environmental Information	1SAC200022H0002
Instrucciones y manuales	1SFC151011M0201
RoHS Information	2CMT2015-005451

### Información de Embalaje

Embalaje Nivel 1 Unidades	bag 10 piece
Embalaje Nivel 1 Ancho	0.1 m
Embalaje Nivel 1 Largo	0.1 m
Embalaje Nivel 1 Alto	0.03 m
Embalaje Nivel 1 Peso	0.24 kg
Embalaje Nivel 1 EAN	7320500245941
Package Level 2 Units	10 piece

### Clasificaciones

Object Classification Code	S
ETIM 4	EC002024 - Accessories for control circuit devices
ETIM 5	EC001029 - Selector switch, complete
ETIM 6	EC001029 - Selector switch, complete
ETIM 7	EC001029 - Selector switch, complete
eClass	V11.0 : 27371243
UNSPSC	39121500
E-Number (Finland)	2312879
E-Number (Norway)	4373494
E-Number (Sweden)	3711302

### Categorías

Productos y sistemas de baja tensión → Aparatos de control → Pulsanería → Compact Range

