

PRODUCT-DETAILS

C3SS1-10B-11**SELECTOR SWITCH C3SS1-10B-11****Información General**

Tipo de producto extendido	C3SS1-10B-11
Código de producto	1SFA619210R1076
EAN	7320500555378
Descripción corta	SELECTOR SWITCH C3SS1-10B-11
Descripción larga	Compact Selector Switch - 3-pos Fixed A&B&C - Short handle - Black - Non-illuminated - Black plastic - 1NO+1NC

Clasificación

Cantidad mínima de pedido	10 piece
Código arancelario	8536501999

Descargas Populares

Ficha técnica, información técnica	1SFC151007C02_
Instrucciones y manuales	1SFC151011M0201

Dimensiones

Ancho del product	0.03 m
Alto del producto	0.03 m

Largo del product	0.072 m
Peso del product	0.024 kg

Technical

Temperatura ambiente	Funcionamiento -25 ... +70 °C Almacenamiento -40 ... +85 °C
Color	Black
Actuator Type	Short handle
Bezel Material	Black Plastic
Illumination	Non-illuminated
Function	Maintained
Sub-Function	3-position
Maintained Positions	A, B, C
Number of Auxiliary Contacts NC	1
Number of Auxiliary Contacts NO	1
Grado de protección	Front IP66 Front IP67 Front IP69K Terminals IP20
Enclosure Type NEMA	Type1 Type12 Type13 Type3R Type4 Type4X
Rated Insulation Voltage (U _i)	300 V
Rated Impulse Withstand Voltage (U _{imp})	6 kV
Rated Frequency (f)	50 / 60 Hz
Rated Operational Voltage	Maximum 300 V AC/DC
Rated Operational Current DC-13 (I _e)	(24 V) 0.3 A (125 V) 0.2 A
Rated Operational Current AC-15 (I _e)	(240 V) 1 A
Power Loss	Maximum 5 W
Mechanical Durability	0.5 million
Connecting Capacity	Flexible with Ferrule 1 x 0.5...1.5 mm ² Flexible with Ferrule 2 x 0.5...1.5 mm ² Flexible with Insulated Ferrule 1 x 0.5...1.5 mm ² Flexible with Insulated Ferrule 2 x 0.5...1.5 mm ² Flexible 1 x 0.5 ...1.5 mm ² Flexible 2 x 0.5 ...1.5 mm ² Solid 1 x 0.5...1.5 mm ² Solid 2 x 0.5...1.5 mm ²
Terminal Type	Screw Terminals
Tightening Torque	0.8 N·m
Wire Stripping Length	6 mm

Technical UL/CSA

Connecting Capacity	1x 22...14 AWG
UL/CSA	2x 22...14 AWG

Ambiente

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
-------------	--

RoHS Date	0626 5
RoHS Information	2CMT2015-005451
Categoría RAEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business

Certificados y Declaraciones (Número de Documento)

CB Certificate	CQC_CN_CN50749
CCC Certificate	2003010305054693_
CQC Certificate	CQC2003010305054693
cURus Certificate	UL_E496500-20171020
Declaration of Conformity - CCC	2020980305001187
Declaración de conformidad - CE	2CMT2015-005451
DNV GL Certificate	9AKK107046A3749
EAC Certificate	RU C-CN.ME77.B.00587/20
Environmental Information	1SAC200022H0002
Instrucciones y manuales	1SFC151011M0201
RoHS Information	2CMT2015-005451

Información de Embalaje

Embalaje Nivel 1 Unidades	bag 10 piece
Embalaje Nivel 1 Ancho	0.1 m
Embalaje Nivel 1 Largo	0.1 m
Embalaje Nivel 1 Alto	0.03 m
Embalaje Nivel 1 Peso	0.24 kg
Embalaje Nivel 1 EAN	7320500246788
Package Level 2 Units	10 piece

Clasificaciones

Object Classification Code	S
ETIM 4	EC002024 - Accessories for control circuit devices
ETIM 5	EC001029 - Selector switch, complete
ETIM 6	EC001029 - Selector switch, complete
ETIM 7	EC001029 - Selector switch, complete
eClass	V11.0 : 27371243
UNSPSC	39121500
E-Number (Finland)	2312905
E-Number (Norway)	4372798
E-Number (Sweden)	3711308

Categorías

Productos y sistemas de baja tensión → Aparatos de control → Pulsanería → Compact Range

