

PRODUCT-DETAILS

CL2-513Y

Compact Pilot Light Yellow LED 110-130V AC



Información General

Tipo de producto extendido	CL2-513Y
Código de producto	1SFA619403R5133
EAN	7320500556252
Descripción corta	Compact Pilot Light Yellow LED 110-130V AC
Descripción larga	Compact Pilot Light - Pilot light head - Yellow - Illuminated - Lamptype: LED 110-130V AC

Clasificación

Cantidad mínima de pedido	10 piece
Código arancelario	8536619090

Descargas Populares

Ficha técnica, información técnica	1SFC151007C02_
Instrucciones y manuales	1SFC151011M0201

Dimensiones

Ancho del product	0.03 m
Alto del producto	0.03 m

Largo del product	0.052 m
Peso del product	0.018 kg

Technical

Temperatura ambiente	Funcionamiento -25 ... +70 °C Almacenamiento -40 ... +85 °C
Color	Yellow
Actuator Type	Pilot light head
Illumination	Illuminated
Lamp Type	110-13 V AC, integrated LED
Grado de protección	Front IP66 Front IP67 Front IP69K Terminals IP20
Enclosure Type NEMA	Type1 Type12 Type13 Type3R Type4 Type4X
Pollution Degree	3
Rated Frequency (f)	Supply Circuit 50 / 60 Hz
Rated Operational Voltage	Supply Circuit 110 ... 130 V AC
Connecting Capacity	Flexible with Ferrule 1 x 0.75...2.5 mm ² Flexible with Ferrule 2 x 0.75...2.5 mm ² Flexible with Insulated Ferrule 1 x 0.75...2.5 mm ² Flexible with Insulated Ferrule 2 x 0.75...2.5 mm ² Flexible 1 x 0.75 ... 2.5 mm ² Flexible 2 x 0.75 ... 2.5 mm ² Solid 1 x 0.75...2.5 mm ² Solid 2 x 0.75...2.5 mm ²
Connection Type	Screw Clamp
Terminal Type	Screw Terminals
Tightening Torque	0.9 N·m
Wire Stripping Length	8 mm

Technical UL/CSA

Connecting Capacity	1x 18...14 AWG
UL/CSA	2x 18...14 AWG

Ambiente

RoHS Status	Following EU Directive 2011/65/EU and Amendment 2015/863 July 22, 2019
RoHS Information	2CMT2015-005451
Categoría RAEE	5. Small Equipment (No External Dimension More Than 50 cm)
WEEE B2C / B2B	Business To Business

Certificados y Declaraciones (Número de Documento)

CB Certificate	CQC_CN_CN50749
CCC Certificate	2003010305054693_
CQC Certificate	CQC2003010305054693
cULus Certificate	UL_E496500-20171020
cURus Certificate	UL_E496500-20171020
Declaration of Conformity - CCC	2020980305001187
Declaración de	2CMT2015-005451

conformidad - CE	
DNV GL Certificate	9AKK107046A3749
EAC Certificate	EAC-RU C-CN.ME77.B.00690_20
Environmental Information	1SAC200026H0002
Instrucciones y manuales	1SFC151011M0201
RoHS Information	2CMT2015-005451

Información de Embalaje

Embalaje Nivel 1 Unidades	bag 10 piece
Embalaje Nivel 1 Ancho	0.125 m
Embalaje Nivel 1 Largo	0.235 m
Embalaje Nivel 1 Alto	0.05 m
Embalaje Nivel 1 Peso	0.184 kg
Embalaje Nivel 1 EAN	7320500475652

Clasificaciones

ETIM 5	EC000272 - Indicator light complete
ETIM 6	EC000272 - Indicator light complete
ETIM 7	EC000272 - Indicator light complete
eClass	V11.0 : 27371223
UNSPSC	39121500
E-Number (Finland)	2313529
E-Number (Norway)	4373522
E-Number (Sweden)	3705763

Categorías

Productos y sistemas de baja tensión → Aparatos de control → Pulsanería → Compact Range → CL

