

PRODUCT-DETAILS

232ERS6W

Wall mounted outlets, 2P+E, 32A, 200 ... 250 V



Información General

Tipo de producto extendido	232ERS6W
Código de producto	2CMA101236R1000
EAN	7392696012362
Descripción corta	Wall mounted outlets, 2P+E, 32A, 200 ... 250 V
Descripción larga	Wall mounted outlet, 2P+E, 32A, 200 ... 250 V Clock Position Of Grounding Contact 6 hour Color code Blue

Clasificación

E-Number (Sweden)	E2417631
E-Number (Finland)	2420224
E-Number (Norway)	1540744
EAN	7392696012362
Country of Origin	Czech Republic (CZ)
Cantidad mínima de pedido	5 piece

Dimensiones

Ancho del product	89 mm
Alto del producto	117 mm
Peso del product	0.31 kg

Información de Embalaje

Embalaje Nivel 1 Ancho	134 mm
Embalaje Nivel 1 Largo	177 mm
Embalaje Nivel 1 Alto	467 mm
Embalaje Nivel 1 Peso	1.55 kg
Embalaje Nivel 1 EAN	7392696020336
Embalaje Nivel 1 Unidades	box 5 piece

Ambiente

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificados y Declaraciones (Número de Documento)

CB Certificate	2CHC660169X0201
Declaración de conformidad - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1616295
REACH Declaration	2CMC700005D0001

Información Adicional

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 6 mm ²
Cable Diameter	25 mm
Cable Entry Position	Other
Color	Blue
Connection Type	Screw
Grado de protección	IP67
Frequency (f)	50 Hz 60 Hz
Function	Wall mounted socket
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#232ERS6W
Mounting Holes	40x63.5, 40x73.5
Mounting Type	Angled
Number of Poles	3
Order Multiple	5 piece
Product Main Type	ERS
Product Name	Wall mounted socket
Protection Type	Watertight
Rated Current (I _n)	32 A
Rated Voltage (U _r)	200 ... 250 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets

Instrucciones y manuales	2CMC700014C0016
Installation Manual	2CMC700014C0016
RAL Number	RAL 7012 - Gris basalto

Clasificaciones

eClass	27440510
UNSPSC	39120000

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categorías

Productos y sistemas de baja tensión → Tomas de corriente industriales → Easy & Safe → Surface Socket Outlets

