

PRODUCT-DETAILS

# 216ERU6W

## Panel mounted socket outlets, 2P+E, 16A, 200 ... 250 V



### Información General

Tipo de producto extendido	216ERU6W
Código de producto	2CMA101291R1000
EAN	7392696012911
Descripción corta	Panel mounted socket outlets, 2P+E, 16A, 200 ... 250 V
Descripción larga	Panel mounted socket outlet, 2P+E, 16A, 200 ... 250 V Clock Position Of Grounding Contact 6 hour Color code Blue

### Clasificación

E-Number (Sweden)	E2417686
E-Number (Finland)	2420234
EAN	7392696012911
Country of Origin	Czech Republic (CZ)
Cantidad mínima de pedido	10 piece

### Dimensiones

Ancho del product	85 mm
Alto del producto	103 mm

Peso del product	0.15 kg
------------------	---------

---

## Información de Embalaje

Embalaje Nivel 1 Ancho	74 mm
Embalaje Nivel 1 Largo	187 mm
Embalaje Nivel 1 Alto	442 mm
Embalaje Nivel 1 Peso	1.5 kg
Embalaje Nivel 1 EAN	7392696051873
Embalaje Nivel 1 Unidades	box 10 piece

---

## Ambiente

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

---

## Certificados y Declaraciones (Número de Documento)

CB Certificate	2CHC660168X0201
Declaración de conformidad - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1616293
REACH Declaration	2CMC700005D0001

---

## Información Adicional

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	1 ... 2.5 mm <sup>2</sup>
Cable Diameter	6 ... 13 mm
Color	Blue
Connection Type	Screw
Grado de protección	IP67
Frequency (f)	50 Hz 60 Hz
Function	Panel mounted socket
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#216ERU6W
Mounting Holes	75x75
Mounting Type	Unified straight flange
Number of Poles	3
Order Multiple	10 piece
Product Main Type	ERU
Product Name	Panel mounted socket
Protection Type	Watertight

Rated Current ( $I_n$ )	16 A
Rated Frequency (f)	50..60 Hz
Rated Voltage ( $U_r$ )	200 ... 250 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instrucciones y manuales	2CMC700014C0016
RAL Number	RAL 7012 - Gris basalto

---

## Clasificaciones

eClass	27440504
UNSPSC	39120000

---

## Technical

Wire Size	14 ... 12 AWG
Tightening Torque	WireClamp0.8 N·m

---

## Categorías

Productos y sistemas de baja tensión → Tomas de corriente industriales → Easy & Safe → Socket Outlets for Panel Mounting

