

PRODUCT-DETAILS

332ERU6W

Panel mounted socket outlets, 3P+E, 32A, 380 ... 415 V



Información General

Tipo de producto extendido	332ERU6W
Código de producto	2CMA101313R1000
EAN	7392696013130
Descripción corta	Panel mounted socket outlets, 3P+E, 32A, 380 ... 415 V
Descripción larga	Panel mounted socket outlet, 3P+E, 32A, 380 ... 415 V Clock Position Of Grounding Contact 6 hour Color code Red

Clasificación

E-Number (Sweden)	E2417708
EAN	7392696013130
Country of Origin	Czech Republic (CZ)
Cantidad mínima de pedido	10 piece

Dimensiones

Ancho del product	85 mm
Alto del product	98 mm
Peso del product	0.23 kg

Información de Embalaje

Embalaje Nivel 1 Ancho	94 mm
Embalaje Nivel 1 Largo	192 mm
Embalaje Nivel 1 Alto	442 mm
Embalaje Nivel 1 Peso	2.3 kg
Embalaje Nivel 1 EAN	7392696051910
Embalaje Nivel 1 Unidades	box 10 piece

Ambiente

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificados y Declaraciones (Número de Documento)

CB Certificate	2CHC660169X0201
Declaración de conformidad - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1616295
REACH Declaration	2CMC700005D0001

Información Adicional

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 6 mm ²
Cable Diameter	13 ... 21.5 mm
Color	Red
Connection Type	Screw
Grado de protección	IP67
Frequency (f)	50 Hz 60 Hz
Function	Panel mounted socket
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#332ERU6W
Mounting Holes	75x75
Mounting Type	Unified straight flange
Number of Poles	4
Order Multiple	10 piece
Product Main Type	ERU
Product Name	Panel mounted socket
Protection Type	Watertight
Rated Current (I _n)	32 A
Rated Frequency (f)	50...60 Hz

Rated Voltage (U_r)	380 ... 415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instrucciones y manuales	2CMC700014C0016
RAL Number	RAL 7012 - Gris basalto

Clasificaciones

eClass	27440504
UNSPSC	39120000

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categorías

Productos y sistemas de baja tensión → Tomas de corriente industriales → Easy & Safe → Socket Outlets for Panel Mounting

