

PRODUCT-DETAILS

332EP9

Industrial Plugs, 3P+E, 32A, 200 ... 250 V



Información General

Tipo de producto extendido	332EP9
Código de producto	2CMA101986R1000
EAN	7392696019866
Descripción corta	Industrial Plugs, 3P+E, 32A, 200 ... 250 V
Descripción larga	Industrial Plugs, 3P+E, 32A, 200 ... 250 V Clock Position Of Grounding Contact 9 hour Color code Blue

Clasificación

E-Number (Sweden)	E2416176
EAN	7392696019866
Country of Origin	Czech Republic (CZ)
Cantidad mínima de pedido	10 piece

Dimensiones

Ancho del product	79 mm
Alto del product	83 mm
Peso del product	0.23 kg

Información de Embalaje

Embalaje Nivel 1 Ancho	154 mm
Embalaje Nivel 1 Largo	182 mm
Embalaje Nivel 1 Alto	378 mm
Embalaje Nivel 1 Peso	2.3 kg
Embalaje Nivel 1 EAN	7392696030182
Embalaje Nivel 1 Unidades	box 10 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	1055 kg
Package Level 2 EAN	7392696066631
Package Level 2 Units	pallet (lift) 450 piece

Ambiente

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificados y Declaraciones (Número de Documento)

CB Certificate	2CHC660167X0201
Declaración de conformidad - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1617364
REACH Declaration	2CMC700005D0001

Información Adicional

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 6 mm ²
Cable Diameter	22 mm
Cable Entry Position	Swivel
Color	Blue
Connection Type	Screw
Grado de protección	IP44
Frequency (f)	50 Hz 60 Hz
Function	Plug
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#332EP9
Number of Poles	4

Order Multiple	10 piece
Product Main Type	EP
Product Name	Industrial Plug
Protection Type	Splashproof
Rated Current (I_n)	32 A
Rated Voltage (U_r)	200 ... 250 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instrucciones y manuales	2CMC700014C0016
RAL Number	RAL 7012 - Gris basalto

Clasificaciones

eClass	27440509
UNSPSC	39120000

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categorías

Productos y sistemas de baja tensión → Tomas de corriente industriales → Easy & Safe → Plugs

