

PRODUCT-DETAILS

# 232EC6

## Industrial Connectors, 2P+E, 32A, 200 ... 250 V



### Información General

Tipo de producto extendido	232EC6
Código de producto	2CMA102031R1000
EAN	7392696020312
Descripción corta	Industrial Connectors, 2P+E, 32A, 200 ... 250 V
Descripción larga	Industrial Connectors, 2P+E, 32A, 200 ... 250 V Clock Position Of Grounding Contact 6 hour Color code Blue

### Clasificación

E-Number (Sweden)	E2416185
E-Number (Finland)	2420089
E-Number (Norway)	1540704
EAN	7392696020312
Country of Origin	Czech Republic (CZ)
Cantidad mínima de pedido	10 piece

### Dimensiones

Ancho del product	79 mm
Alto del producto	93 mm
Peso del product	0.26 kg

## Información de Embalaje

Embalaje Nivel 1 Ancho	154 mm
Embalaje Nivel 1 Largo	182 mm
Embalaje Nivel 1 Alto	378 mm
Embalaje Nivel 1 Peso	2.6 kg
Embalaje Nivel 1 EAN	7392696030632
Embalaje Nivel 1 Unidades	box 10 piece

## Ambiente

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

## Certificados y Declaraciones (Número de Documento)

CB Certificate	2CHC660166X0201
Declaración de conformidad - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1617363
REACH Declaration	2CMC700005D0001

## Información Adicional

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 6 mm <sup>2</sup>
Cable Diameter	22 mm
Cable Entry Position	Swivel
Color	Blue
Connection Type	Screw
Grado de protección	IP44
Frequency (f)	50 Hz 60 Hz
Function	Connector
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#232EC6
Number of Poles	3
Order Multiple	10 piece
Product Main Type	EC
Product Name	Industrial Connector
Protection Type	Splashproof
Rated Current (I <sub>n</sub> )	32 A
Rated Voltage (U <sub>r</sub> )	200 ... 250 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instrucciones y manuales	2CMC700014C0016
RAL Number	RAL 7012 - Gris basalto

---

## Clasificaciones

---

eClass	27440509
UNSPSC	39120000

---

---

## Technical

---

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

---

---

## Categorías

---

Productos y sistemas de baja tensión → Tomas de corriente industriales → Easy & Safe → Connectors

