

PRODUCT-DETAILS

332RS6W

332RS6W Wall mounted socket



Información General

Tipo de producto extendido	332RS6W
Código de producto	2CMA167180R1000
EAN	7392696671804
Descripción corta	332RS6W Wall mounted socket
Descripción larga	Surface socket-outlet, earthing sleeve position 6h, rated current 32A, IP67 watertight, 3-poles+earth, frequency 50-60 Hz, color code Red

Clasificación

E-Number (Sweden)	E2416555
E-Number (Finland)	2421218
E-Number (Norway)	1543443
EAN	7392696671804
Country of Origin	Czech Republic (CZ)
Cantidad mínima de pedido	1 piece

Dimensiones

Ancho del product	99 mm
Alto del producto	178 mm
Peso del product	0.512 kg
Mechanical Drawings	9AKK107991A3823

Información de Embalaje

Embalaje Nivel 1 Ancho	135 mm
Embalaje Nivel 1 Largo	140 mm
Embalaje Nivel 1 Alto	200 mm
Embalaje Nivel 1 Peso	0.6 kg
Embalaje Nivel 1 EAN	7392696671804
Embalaje Nivel 1 Unidades	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	124.4 kg
Package Level 2 EAN	7392696072137
Package Level 2 Units	pallet (lift) 174 piece

Ambiente

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificados y Declaraciones (Número de Documento)

Declaración de conformidad - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1613211
REACH Declaration	2CMC700005D0001

Información Adicional

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 10 mm ²
Cable Diameter	25 mm
Cable Entry Position	Cable entry Ø 25mm
Color	Red
Connection Type	Screw
Grado de protección	IP67 IP69
Frequency (f)	50 Hz 60 Hz
Function	Surface socket outlet
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#332RS6W
Mounting Holes	60x148,2
Number of Poles	4
Order Multiple	1 piece
Product Main Type	TRS
Product Name	Wall mounted socket
Protection Type	Watertight
Rated Current (I _n)	32 A
Rated Voltage (U _r)	380 ... 415 V

Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Surface Socket Outlets
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instrucciones y manuales	2CMC700014C0016
Installation Manual	2CMC700014C0016
RAL Number	RAL 7012 - Gris basalto

Clasificaciones

eClass	27440510
UNSPSC	39120000

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categorías

Productos y sistemas de baja tensión → Tomas de corriente industriales → Tough & Safe → Surface Socket Outlets

