

PRODUCT-DETAILS

363RS6W

363RS6W Wall mounted socket



Información General

Tipo de producto extendido	363RS6W
Código de producto	2CMA167316R1000
EAN	7392696673167
Descripción corta	363RS6W Wall mounted socket
Descripción larga	Surface socket-outlet, earthing sleeve position 6h, rated current 63A, IP67 watertight, 3-poles+earth, frequency 50-60 Hz, color code Red

Clasificación

E-Number (Sweden)	E2416575
E-Number (Finland)	2421228
E-Number (Norway)	1543473
EAN	7392696673167
Country of Origin	Czech Republic (CZ)
Cantidad mínima de pedido	1 piece

Dimensiones

Ancho del product	118 mm
Alto del producto	263 mm
Peso del product	1.07 kg
Mechanical Drawings	9AKK107991A3824

Información de Embalaje

Embalaje Nivel 1 Ancho	152 mm
Embalaje Nivel 1 Largo	120 mm
Embalaje Nivel 1 Alto	265 mm
Embalaje Nivel 1 Peso	1.18 kg
Embalaje Nivel 1 EAN	7392696673167
Embalaje Nivel 1 Unidades	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	167.5 kg
Package Level 2 EAN	7392696072892
Package Level 2 Units	pallet (lift) 125 piece

Ambiente

RoHS Status	Following EU Directive 2011/65/EU
SCIP	28654517-b610-4266-b2d1-dd44d2b3a2c2 Czech Republic (CZ)

Certificados y Declaraciones (Número de Documento)

Declaración de conformidad - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
REACH Declaration	2CMC700005D0001

Información Adicional

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	6 ... 25 mm ²
Cable Entry Position	Other
Color	Red
Connection Type	Screw
Grado de protección	IP67 IP69
Frequency (f)	50 Hz 60 Hz
Function	Surface socket outlet
Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#363RS6W
Mounting Holes	176x76
Number of Poles	4
Order Multiple	1 piece
Product Main Type	TRS
Product Name	Wall mounted socket
Protection Type	Watertight
Rated Current (I _N)	63 A
Rated Voltage (U _r)	380 ... 415 V
Recommended Screw Driver	PH2

Standards	IEC 60309-1, -2
Suitable For	Surface Socket Outlets
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instrucciones y manuales	2CMC000038M0001
Installation Manual	2CMC000038M0001
RAL Number	RAL 7012 - Gris basalto

Clasificaciones

eClass	27440510
UNSPSC	39120000

Technical

Wire Size	8 ... 4 AWG
Tightening Torque	WireClamp3.5 N·m

Categorías

Productos y sistemas de baja tensión → Tomas de corriente industriales → Tough & Safe → Surface Socket Outlets

