


PRODUCT-DETAILS

# 363RAU6W

## 363RAU6W Panel mounted socket



### Información General

Tipo de producto extendido	363RAU6W
Código de producto	2CMA167452R1000
EAN	7392696674522
Descripción corta	363RAU6W Panel mounted socket
Descripción larga	Socket-outlet, panel mounting, earthing sleeve position 6h, rated current 63A, IP67 watertight, unified flange, angled, 3-poles+earth, frequency 50-60 Hz, color code Red

### Clasificación

E-Number (Sweden)	E2416763
E-Number (Finland)	2421283
E-Number (Norway)	1562073
EAN	7392696674522
Country of Origin	Czech Republic (CZ)
Cantidad mínima de pedido	1 piece

### Dimensiones

Ancho del product	106 mm
-------------------	--------

Alto del producto	147 mm
Peso del product	0.63 kg
Mechanical Drawings	9AKK107991A3796

## Información de Embalaje

Embalaje Nivel 1 Ancho	112 mm
Embalaje Nivel 1 Largo	112 mm
Embalaje Nivel 1 Alto	139 mm
Embalaje Nivel 1 Peso	0.63 kg
Embalaje Nivel 1 EAN	7392696674522
Embalaje Nivel 1 Unidades	box 1 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	240.5 kg
Package Level 2 EAN	7392696073226
Package Level 2 Units	pallet (lift) 350 piece

## Ambiente

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

## Certificados y Declaraciones (Número de Documento)

Declaración de conformidad - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1614204
REACH Declaration	2CMC700005D0001

## Información Adicional

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	6 ... 25 mm <sup>2</sup>
Cable Diameter	17 ... 35 mm
Color	Red
Connection Type	Screw
Grado de protección	IP67 IP69
Frequency (f)	50 Hz 60 Hz
Function	Socket outlet, panel mounting, unified flange, angled

Housing Material	Thermoplastic (PBT)
Invoice Description	Ind. P&S#363RAU6W
Mounting Holes	84x80
Mounting Type	unified flange, angled
Number of Poles	4
Order Multiple	1 piece
Product Main Type	TRAU
Product Name	Panel mounted socket
Protection Type	Watertight
Rated Current ( $I_n$ )	63 A
Rated Frequency (f)	50...60 Hz
Rated Voltage ( $U_r$ )	380 ... 415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Socket Outlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instrucciones y manuales	2CMC000038M0001
Installation Manual	2CMC000038M0001
RAL Number	RAL 7001 - Gris plata

---

## Clasificaciones

eClass	27440504
UNSPSC	39120000

---

## Technical

Wire Size	8 ... 4 AWG
Tightening Torque	WireClamp3.5 N·m

---

## Categorías

Productos y sistemas de baja tensión → Tomas de corriente industriales → Tough & Safe → Socket Outlets for Panel Mounting

