


PRODUCT-DETAILS

# 463RAU6W

## 463RAU6W Panel mounted socket



### Información General

|                            |   |
|----------------------------|---|
| Tipo de producto extendido | 463RAU6W  |
| Código de producto         | 2CMA167464R1000   |
| EAN                        | 7392696674645   |
| Descripción corta          | 463RAU6W Panel mounted socket   |
| Descripción larga          | Socket-outlet, panel mounting, earthing sleeve position 6h, rated current 63A, IP67 watertight, unified flange, angled, 3-poles+neutral+earth, frequency 50-60 Hz, color code Red |

### Clasificación

|                           |                     |
|---------------------------|---------------------|
| E-Number (Sweden)         | E2416769            |
| E-Number (Finland)        | 2421759             |
| E-Number (Norway)         | 1562083             |
| EAN                       | 7392696674645       |
| Country of Origin         | Czech Republic (CZ) |
| Cantidad mínima de pedido | 1 piece             |

### Dimensiones

|                   |        |
|-------------------|--------|
| Ancho del product | 106 mm |
|-------------------|--------|

|                     |                 |
|---------------------|-----------------|
| Alto del producto   | 147 mm          |
| Peso del product    | 0.63 kg         |
| Mechanical Drawings | 9AKK107991A3798 |

## Información de Embalaje

|                                |                         |
|--------------------------------|-------------------------|
| Embalaje Nivel 1 Ancho         | 112 mm                  |
| Embalaje Nivel 1 Largo         | 112 mm                  |
| Embalaje Nivel 1 Alto          | 139 mm                  |
| Embalaje Nivel 1 Peso          | 0.63 kg                 |
| Embalaje Nivel 1 EAN           | 7392696674645           |
| Embalaje Nivel 1 Unidades      | box 1 piece             |
| Package Level 2 Width          | 800 mm                  |
| Package Level 2 Depth / Length | 1200 mm                 |
| Package Level 2 Height         | 900 mm                  |
| Package Level 2 Gross Weight   | 240.5 kg                |
| Package Level 2 EAN            | 7392696073288           |
| Package Level 2 Units          | pallet (lift) 350 piece |

## Ambiente

|             |                                   |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

## Certificados y Declaraciones (Número de Documento)

|                                 |                 |
|---------------------------------|-----------------|
| Declaración de conformidad - CE | 2CMC700005D0001 |
| Environmental Information       | 2CMC000056M0000 |
| RoHS Information                | 2CMC700005D0001 |
| SEMKO Certificate               | 1614204         |
| REACH Declaration               | 2CMC700005D0001 |

## Información Adicional

|                        |   |
|------------------------|---|
| Additional Information | 3P+N+E  |
| Ambient Temperature    | -25 ... 40 °C   |
| Cable Cross-Section    | 6 ... 25 mm <sup>2</sup>                              |
| Cable Diameter         | 17 ... 35 mm  |
| Color                  | Red   |
| Connection Type        | Screw   |
| Grado de protección    | IP67<br>IP69  |
| Frequency (f)          | 50 Hz<br>60 Hz  |
| Function               | Socket outlet, panel mounting, unified flange, angled |

|                            |                                   |
|----------------------------|-----------------------------------|
| Housing Material           | Thermoplastic (PBT)               |
| Invoice Description        | Ind. P&S#463RAU6W                 |
| Mounting Holes             | 84x80                             |
| Mounting Type              | unified flange, angled            |
| Number of Poles            | 5                                 |
| Order Multiple             | 1 piece                           |
| Product Main Type          | TRAU                              |
| Product Name               | Panel mounted socket              |
| Protection Type            | Watertight                        |
| Rated Current ( $I_n$ )    | 63 A                              |
| Rated Frequency (f)        | 50...60 Hz                        |
| Rated Voltage ( $U_r$ )    | 200/346 ... 240/415 V             |
| Recommended Screw Driver   | PH2                               |
| Standards                  | IEC 60309-1, -2                   |
| Suitable For               | Socket Outlets for Panel Mounting |
| Suitable for Product Class | IEC Industrial Plugs and Sockets  |
| Instrucciones y manuales   | 2CMC000038M0001                   |
| Installation Manual        | 2CMC000038M0001                   |
| RAL Number                 | RAL 7001 - Gris plata             |

---

## Clasificaciones

|        |          |
|--------|----------|
| eClass | 27440504 |
| UNSPSC | 39120000 |

---

## Technical

|                   |                  |
|-------------------|------------------|
| Wire Size         | 8 ... 4 AWG      |
| Tightening Torque | WireClamp3.5 N·m |

---

## Categorías

Productos y sistemas de baja tensión → Tomas de corriente industriales → Tough & Safe → Socket Outlets for Panel Mounting

