


PRODUCT-DETAILS

## 232RAM6

Socket-outlet, panel mounting, 6h, 32A, IP44, minimized flange, angled, 2P+E



### Información General

Tipo de producto extendido	232RAM6
Código de producto	2CMA170027R1000
EAN	7392696700276
Descripción corta	Socket-outlet, panel mounting, 6h, 32A, IP44, minimized flange, angled, 2P+E
Descripción larga	Panel mounted socket, earthing sleeve position 6h, rated current 32A, IP44 splashproof, minimized flange, angled, 2-poles+earth, frequency 50-60 Hz, color code Blue

### Clasificación

E-Number (Sweden)	E2416480
E-Number (Finland)	2421410
E-Number (Norway)	2416480
EAN	7392696700276
Country of Origin	Czech Republic (CZ)
Cantidad mínima de pedido	10 piece

### Dimensiones

Ancho del product	94 mm
Alto del producto	99 mm
Peso del product	0.27 kg
Mechanical Drawings	9AKK107991A3699

---

## Información de Embalaje

Embalaje Nivel 1 Ancho	188 mm
Embalaje Nivel 1 Largo	175 mm
Embalaje Nivel 1 Alto	428 mm
Embalaje Nivel 1 Peso	2.7 kg
Embalaje Nivel 1 EAN	7392696702256
Embalaje Nivel 1 Unidades	box 10 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	668 kg
Package Level 2 EAN	7392696077927
Package Level 2 Units	pallet (lift) 240 piece

---

## Ambiente

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

---

## Certificados y Declaraciones (Número de Documento)

CB Certificate	2CHC660154X0201
Declaración de conformidad - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1614201
REACH Declaration	2CMC700005D0001

---

## Información Adicional

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 10 mm <sup>2</sup>
Cable Diameter	13 ... 21.5 mm
Color	Blue
Connection Type	Screw
Grado de protección	IP44
Frequency (f)	50 Hz 60 Hz
Function	Panel mounted socket
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#232RAM6
Mounting Holes	75x75
Mounting Type	Minimized angled flange
Number of Poles	3
Order Multiple	10 piece
Product Main Type	ERAM
Product Name	Panel mounted socket

Protection Type	Splashproof
Rated Current ( $I_n$ )	32 A
Rated Frequency (f)	50...60 Hz
Rated Voltage ( $U_r$ )	200 ... 250 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Socket Outlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instrucciones y manuales	2CMC700014C0016
RAL Number	RAL 7001 - Gris plata

## Clasificaciones

eClass	27440504
UNSPSC	39121406

## Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

## Categorías

Productos y sistemas de baja tensión → Tomas de corriente industriales → Easy & Safe → Socket Outlets for Panel Mounting

