

PRODUCT-DETAILS

332RAM6

Socket-outlet, panel mounting, 6h, 32A, IP44, minimized flange, angled, 3P+E



Información General

Tipo de producto extendido	332RAM6
Código de producto	2CMA170035R1000
EAN	7392696700351
Descripción corta	Socket-outlet, panel mounting, 6h, 32A, IP44, minimized flange, angled, 3P+E
Descripción larga	Panel mounted socket, earthing sleeve position 6h, rated current 32A, IP44 splashproof, minimized flange, angled, 3-poles+earth, frequency 50-60 Hz, color code Red

Clasificación

E-Number (Sweden)	E2416483
E-Number (Finland)	2421413
E-Number (Norway)	2416483
EAN	7392696700351
Country of Origin	Czech Republic (CZ)
Cantidad mínima de pedido	10 piece

Dimensiones

Ancho del product	94 mm
-------------------	-------

Alto del producto	100 mm
Peso del product	0.22 kg
Mechanical Drawings	9AKK107991A3701

Información de Embalaje

Embalaje Nivel 1 Ancho	188 mm
Embalaje Nivel 1 Largo	175 mm
Embalaje Nivel 1 Alto	428 mm
Embalaje Nivel 1 Peso	2.2 kg
Embalaje Nivel 1 EAN	7392696702331
Embalaje Nivel 1 Unidades	box 10 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	548 kg
Package Level 2 EAN	7392696077958
Package Level 2 Units	pallet (lift) 240 piece

Ambiente

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificados y Declaraciones (Número de Documento)

CB Certificate	2CHC660154X0201
Declaración de conformidad - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1614201
REACH Declaration	2CMC700005D0001

Información Adicional

Additional Information	3P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 10 mm ²
Cable Diameter	13 ... 21.5 mm
Color	Red
Connection Type	Screw
Grado de protección	IP44
Frequency (f)	50 Hz 60 Hz
Function	Panel mounted socket

Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#332RAM6
Mounting Holes	75x75
Mounting Type	Minimized angled flange
Number of Poles	4
Order Multiple	10 piece
Product Main Type	ERAM
Product Name	Panel mounted socket
Protection Type	Splashproof
Rated Current (I_n)	32 A
Rated Frequency (f)	50...60 Hz
Rated Voltage (U_r)	380 ... 415 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Socket Outlets for Panel Mounting
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instrucciones y manuales	2CMC700014C0016
RAL Number	RAL 7001 - Gris plata

Clasificaciones

eClass	27440504
UNSPSC	39121406

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categorías

Productos y sistemas de baja tensión → Tomas de corriente industriales → Easy & Safe → Socket Outlets for Panel Mounting

