

PRODUCT-DETAILS

316RS6

Surface socket-outlet, 6h, 16A, IP44, 3P+E



Información General

| | |
|----------------------------|--|
| Tipo de producto extendido | 316RS6 |
| Código de producto | 2CMA193106R1000 |
| EAN | 7392696931069 |
| Descripción corta | Surface socket-outlet, 6h, 16A, IP44, 3P+E |
| Descripción larga | Wall mounted socket, earthing sleeve position 6h, rated current 16A, IP44 splashproof, 3-poles+earth, frequency 50-60 Hz, color code Red |

Clasificación

| | |
|---------------------------|---------------------|
| E-Number (Sweden) | E2416449 |
| E-Number (Finland) | 2421203 |
| E-Number (Norway) | 1542313 |
| EAN | 7392696931069 |
| Country of Origin | Czech Republic (CZ) |
| Cantidad mínima de pedido | 10 piece |

Dimensiones

| | |
|---------------------|-----------------|
| Ancho del product | 79 mm |
| Alto del producto | 79 mm |
| Peso del product | 0.24 kg |
| Mechanical Drawings | 9AKK107991A3808 |

Información de Embalaje

| | |
|--------------------------------|-------------------------|
| Embalaje Nivel 1 Ancho | 154 mm |
| Embalaje Nivel 1 Largo | 182 mm |
| Embalaje Nivel 1 Alto | 378 mm |
| Embalaje Nivel 1 Peso | 2.4 kg |
| Embalaje Nivel 1 EAN | 7392696661065 |
| Embalaje Nivel 1 Unidades | box 10 piece |
| Package Level 2 Width | 800 mm |
| Package Level 2 Depth / Length | 1200 mm |
| Package Level 2 Height | 900 mm |
| Package Level 2 Gross Weight | 1100 kg |
| Package Level 2 EAN | 7392696079136 |
| Package Level 2 Units | pallet (lift) 450 piece |

Ambiente

| | |
|-------------|-----------------------------------|
| RoHS Status | Following EU Directive 2011/65/EU |
|-------------|-----------------------------------|

Certificados y Declaraciones (Número de Documento)

| | |
|---------------------------------|-----------------|
| Declaración de conformidad - CE | 2CMC700005D0001 |
| Environmental Information | 2CMC000056M0000 |
| RoHS Information | 2CMC700005D0001 |
| SEMKO Certificate | 1613211 |
| REACH Declaration | 2CMC700005D0001 |

Información Adicional

| | |
|---------------------------------|---|
| Additional Information | 3P+E |
| Ambient Temperature | -25 ... 40 °C |
| Cable Cross-Section | 1.5 ... 4 mm ² |
| Cable Diameter | 18 mm |
| Cable Entry Position | Cable entry, flexible membrane and metric threaded M20 insert for top cable entry.Rear knock-out cable entry. |
| Color | Red |
| Connection Type | Screw |
| Grado de protección | IP44 |
| Frequency (f) | 50 Hz 60 Hz |
| Function | Wall mounted socket |
| Housing Material | Plastic (PA) |
| Invoice Description | Ind. P&S#316RS6 |
| Mounting Holes | 91x67 |
| Mounting Type | Angled |
| Number of Poles | 4 |
| Order Multiple | 10 piece |
| Product Main Type | ERS |
| Product Name | Wall mounted socket |
| Protection Type | Splashproof |
| Rated Current (I _n) | 16 A |

| | |
|---------------------------------|----------------------------------|
| Rated Voltage (U _r) | 380 ... 415 V |
| Recommended Screw Driver | PH2 |
| Standards | IEC 60309-1, -2 |
| Suitable For | Surface Socket Outlets |
| Suitable for Product Class | IEC Industrial Plugs and Sockets |
| Instrucciones y manuales | 2CMC700014C0016 |
| Installation Manual | 2CMC700014C0016 |
| RAL Number | RAL 7012 - Gris basalto |

Clasificaciones

| | |
|--------|----------|
| eClass | 27440510 |
| UNSPSC | 39121406 |

Technical

| | |
|-------------------|------------------|
| Wire Size | 14 ... 12 AWG |
| Tightening Torque | WireClamp0.8 N·m |

Categorías

Productos y sistemas de baja tensión → Tomas de corriente industriales → Easy & Safe → Surface Socket Outlets

