

PRODUCT-DETAILS

232RS6

Surface socket-outlet, 6h, 32A, IP44, 2P+E



Información General

Tipo de producto extendido	232RS6
Código de producto	2CMA193122R1000
EAN	7392696931229
Descripción corta	Surface socket-outlet, 6h, 32A, IP44, 2P+E
Descripción larga	Wall mounted socket, earthing sleeve position 6h, rated current 32A, IP44 splashproof, 2-poles+earth, frequency 50-60 Hz, color code Blue

Clasificación

E-Number (Sweden)	E2416491
E-Number (Finland)	2421212
E-Number (Norway)	1542332
EAN	7392696931229
Country of Origin	Czech Republic (CZ)
Cantidad mínima de pedido	10 piece

Dimensiones

Ancho del product	85 mm
Alto del producto	118 mm
Peso del product	0.3 kg
Mechanical Drawings	9AKK107991A3804

Información de Embalaje

Embalaje Nivel 1 Ancho	188 mm
Embalaje Nivel 1 Largo	175 mm
Embalaje Nivel 1 Alto	428 mm
Embalaje Nivel 1 Peso	3 kg
Embalaje Nivel 1 EAN	7392696661225
Embalaje Nivel 1 Unidades	box 10 piece
Package Level 2 Width	800 mm
Package Level 2 Depth / Length	1200 mm
Package Level 2 Height	900 mm
Package Level 2 Gross Weight	740 kg
Package Level 2 EAN	7392696079259
Package Level 2 Units	pallet (lift) 240 piece

Ambiente

RoHS Status	Following EU Directive 2011/65/EU
-------------	-----------------------------------

Certificados y Declaraciones (Número de Documento)

Declaración de conformidad - CE	2CMC700005D0001
Environmental Information	2CMC000056M0000
RoHS Information	2CMC700005D0001
SEMKO Certificate	1613211
REACH Declaration	2CMC700005D0001

Información Adicional

Additional Information	2P+E
Ambient Temperature	-25 ... 40 °C
Cable Cross-Section	2.5 ... 10 mm ²
Cable Diameter	22 mm
Cable Entry Position	Cable entry, flexible membrane and metric threaded M25 insert for top cable entry.Rear knock-out cable entry.
Color	Blue
Connection Type	Screw
Grado de protección	IP44
Frequency (f)	50 Hz 60 Hz
Function	Wall mounted socket
Housing Material	Plastic (PA)
Invoice Description	Ind. P&S#232RS6
Mounting Holes	111x72
Mounting Type	Angled
Number of Poles	3
Order Multiple	10 piece
Product Main Type	ERS
Product Name	Wall mounted socket
Protection Type	Splashproof
Rated Current (I _n)	32 A

Rated Voltage (U _r)	200 ... 250 V
Recommended Screw Driver	PH2
Standards	IEC 60309-1, -2
Suitable For	Surface Socket Outlets
Suitable for Product Class	IEC Industrial Plugs and Sockets
Instrucciones y manuales	2CMC700014C0016
Installation Manual	2CMC700014C0016
RAL Number	RAL 7012 - Gris basalto

Clasificaciones

eClass	27440510
UNSPSC	39121406

Technical

Wire Size	12 ... 10 AWG
Tightening Torque	WireClamp1.2 N·m

Categorías

Productos y sistemas de baja tensión → Tomas de corriente industriales → Easy & Safe → Surface Socket Outlets

