

PRODUCT-DETAILS

F202 A-63/0.03

F202 A-63/0.03 Interruptor diferencial



Información General

| | |
|----------------------------|--|
| Tipo de producto extendido | F202 A-63/0.03 |
| Código de producto | 2CSF202101R1630 |
| EAN | 8012542782704 |
| Descripción corta | F202 A-63/0.03 Interruptor diferencial |
| Descripción larga | The RCCBs F200 series assures protection to people and installations against fault current to earth. A large offer for standard instantaneous and selective AC and A types is completed with some configurations for special applications. |

Technical

| | |
|---|-------------------------|
| Standards | IEC/EN 61008 UL 1053 |
| Type of Residual Current | A type |
| Rated Voltage (U_r) | 230 V |
| Rated Operational Voltage | 230 V |
| Rated Insulation Voltage (U_i) | 500 V |
| Rated Impulse Withstand Voltage (U_{imp}) | 4 kV |
| Input Voltage Type | AC |
| Rated Current (I_n) | 63 A |

| | |
|--|--|
| Rated Residual Current | 30 mA |
| Rated Conditional Short-Circuit Current (I_{nc}) | 10 kA |
| Rated Service Short-Circuit Breaking Capacity (I_{cs}) | 1 kA |
| Leakage Current Type | A |
| Rated Frequency (f) | 50 / 60 Hz |
| Power Loss | at Rated Operating Conditions per Pole 3.2 W |
| Power Supply Connection | Arbitrary |
| Electrical Endurance | 10000 cycle |
| Number of Poles | 2 |
| Operating Characteristic | Instantaneous |
| Mounting Type | DIN rail |
| Options Provided | None |
| Accessories Available | Yes |
| Connecting Capacity | Busbar 10 mm ² Rigid 25 ... 25 mm ² Flexible 25 ... 25 mm ² |
| Rated Cross-Section | 4 - Multi-Wired 0...25 mm ² 1 - Solid-Core 25...25 mm ² |

Ambiente

| | |
|--|---|
| Ambient Temperature | -25...55 °C |
| Temperatura ambiente | Funcionamiento -25...55 °C |
| Grado de protección | IP2X |
| Pollution Degree | 2 |
| Resistance to Vibrations acc. to IEC 60068-2-6 | 0.1 mm or 1 g - 20 cycles at 5...150...5 Hz |
| Resistance to Shock acc. to IEC 60068-2-27 | 25g / 2 shocks / 13 ms |
| RoHS Status | Following EU Directive 2011/65/EU |
| Environmental Information | Refer to RoHS |

Technical UL/CSA

| | |
|-------------------------------------|----------|
| Maximum Operating Voltage UL/CSA | 277 V AC |
| Short-Circuit Current Rating (SCCR) | 30 mA |

Dimensiones

| | |
|-------------------------------------|----------|
| Width in Number of Modular Spacings | 2 |
| Ancho del product | 0.035 m |
| Alto del producto | 0.085 m |
| Largo del product | 0.069 m |
| Peso del product | 0.200 kg |

| | |
|----------------------------------|-------|
| Built-In Depth (t ₂) | 69 mm |
|----------------------------------|-------|

Información de Embalaje

| | |
|--------------------------------|---------------|
| Embalaje Nivel 1 Unidades | box 1 piece |
| Embalaje Nivel 1 Ancho | 80 mm |
| Embalaje Nivel 1 Alto | 41 mm |
| Embalaje Nivel 1 Largo | 94 mm |
| Embalaje Nivel 1 Peso | 0.235 kg |
| Embalaje Nivel 1 EAN | 8012542782704 |
| Package Level 2 Units | box 6 piece |
| Package Level 2 Width | 96 mm |
| Package Level 2 Height | 85 mm |
| Package Level 2 Depth / Length | 240 mm |
| Package Level 2 Gross Weight | 1350 g |
| Package Level 2 EAN | 8012542782711 |

Clasificación

| | |
|---------------------------|------------|
| Cantidad mínima de pedido | 1 piece |
| Código arancelario | 85363030 |
| E-Number (Finland) | 3259246 |
| E-Number (Sweden) | 2160117 |
| Country of Origin | Italy (IT) |

Certificados y Declaraciones (Número de Documento)

| | |
|---------------------------------|-----------------|
| Declaración de conformidad - CE | 9AKK106713A5602 |
| Environmental Information | Refer to RoHS |
| Instrucciones y manuales | 9AKK107991A6127 |
| RoHS Information | 2CSC423001K2702 |

Descargas Populares

| | |
|------------------------------------|-----------------|
| Ficha técnica, información técnica | 9AKK107991A8329 |
| Instrucciones y manuales | 9AKK107991A6127 |

Clasificaciones

| | |
|--------------------|--|
| ETIM 7 | EC000003 - Residual current circuit breaker (RCCB) |
| ETIM 8 | EC000003 - Residual current circuit breaker (RCCB) |
| EPLAN Catalog Tree | Electrical engineering / Protection devices / Ground fault current circuit breaker |
| EPLAN Function | Ground fault current circuit-breaker / Ground fault current circuit breakers, 4 |

| | |
|----------------------------|--|
| Definition | connection points / Ground fault current circuit breaker, two-pole 1/2 2/1 3/4 4/3 |
| Categoría RAEE | 5. Small Equipment (No External Dimension More Than 50 cm) |
| WEEE B2C / B2B | Business To Consumer |
| CN8 | 85363030 |
| Object Classification Code | F |

Categorías

Productos y sistemas de baja tensión → Aparatos modulares de instalación → Interruptores diferenciales → Interruptores diferenciales

