

PRODUCT-DETAILS

# ACS310-03E-25A4-4

## ACS310-03E-25A4-4Pn 11, I2n 25,4A IP20



### Información General

Global Commercial Alias	ACS310-03E-25A4-4
Código de producto	3AUA0000039635
ABB Type Designation	ACS310-03E-25A4-4
EAN	6410038785819
Descripción corta	ACS310-03E-25A4-4Pn 11, I2n 25,4A IP20
Descripción larga	The ACS310 drives are designed for squared torque applications such as booster pumps and supply and return fans. The drive includes a powerful and beneficial set of features designed for pump and fan applications. These features include built-in PID controllers and pump and fan control (PFC) that varies the drive's performance in response to changes in pressure, flow or other external data.

### Clasificación

Country of Origin	China (CN) Finland (FI)
Código arancelario	85044088
Invoice Description	ACS310-03E-25A4-4Pn 11, I2n 25,4A IP20
Made To Order	No
Cantidad mínima de pedido	1 piece
Order Multiple	1 piece
Quote Only	No

Selling Unit of Measure	piece
-------------------------	-------

---

## Dimensiones

Peso del product	3.6 kg
Largo del product	217 mm
Alto del producto	344 mm
Ancho del product	226 mm
Embalaje Nivel 1 Unidades	1 carton

---

## Technical

Number of Phases	3
Grado de protección	IP20
Enclosure Type NEMA	Open Type
Frequency (f)	50/60 Hz
Input Voltage ( $U_{in}$ )	380 ... 480 V
Mounting Type	Module for cabinet building
Communication Protocol	MODBUS
Number of Hardware Interfaces	Industrial Ethernet 0 PROFINET 0 RS-232 1 RS-422 0 RS-485 1 Serial TTY 0 USB 0 Parallel 0 Other 1
Includes	With control unit Without optical interface With PC connection
Analog Inputs	2
Analog Outputs	1
Number of Digital In/Outputs	5/1
Output Current, Light- Overload Use	23.1 A
Output Current, Normal Use	25.4 A
Output Power, Light- Overload Use	11 kW
Output Power, Normal Use	11 kW
Apparent Power Output	18 kV·A
Efficiency Level	IE2
Standby Loss	11 W
Complete Drive Module Efficiency (61800-9-2)	

Operating Point Frequency / Current	Absolute Loss	Relative Loss	Efficiency
0 / 25 %	122 W	0.7 %	88.4 %
0 / 50 %	157 W	0.9 %	92.0 %
0 / 100 %	278 W	1.6 %	92.8 %
50 / 25 %	131 W	0.7 %	93.7 %
50 / 50 %	176 W	1.0 %	95.5 %
50 / 100 %	322 W	1.8 %	95.9 %
90 / 50 %	204 W	1.2 %	97.1 %
90 / 100 %	390 W	2.2 %	97.2 %

Temperature Rating

Maximum 40 °C

## Información Adicional

Product Main Type

ACS310

Product Name

Frequency converter

## Clasificaciones

Product Series

ACS310

ETIM 7

EC001857 - Frequency converter =&lt; 1 kV

UNSPSC

39122001

## Ambiente

SCIP

e6d5d8a1-6fda-4f06-be32-c8f10666cd62 Finland (FI)

Categoría RAEE

5. Small Equipment (No External Dimension More Than 50 cm)

## Categorías

Convertidores de frecuencia → Convertidores de frecuencia de baja tensión de CA → Convertidores de frecuencia de propósito general  
 ABB → ACS310 - Drive module for pumps and fans

