

PRODUCT-DETAILS

# ACS355-03E-13A3-2

ACS355-03E-13A3-2 Pn 3,0kW, I2n 13,3A IP20.



## Información General

Global Commercial Alias	ACS355-03E-13A3-2
Código de producto	3AUA0000058177
ABB Type Designation	ACS355-03E-13A3-2
EAN	6438177223528
Descripción corta	ACS355-03E-13A3-2 Pn 3,0kW, I2n 13,3A IP20.
Descripción larga	<p>The ACS355 drives are designed to meet the requirements of an extensive range of machinery applications in food and beverage, material handling, lifting, textile, printing, rubber and plastics, and woodworking applications.</p> <p>The drive is user-friendly, yet it provides a wide range of built-in technology such as the safe torque off functionality and sequence programming, reducing the need for additional control electronics. The product offers options and diverse functionality to cater to the needs set for speed and torque control of AC induction and permanent magnet motors.</p>

## Clasificación

Country of Origin	China (CN) Finland (FI)
Código arancelario	85044084
Invoice Description	ACS355-03E-13A3-2 Pn 3,0kW, I2n 13,3A IP20.
Made To Order	No
Cantidad mínima de pedido	1 piece
Order Multiple	1 piece
Quote Only	No
Selling Unit of Measure	piece

---

## Dimensiones

Peso del product	2.4 kg
Largo del product	217 mm
Alto del producto	344 mm
Ancho del product	166 mm
Embalaje Nivel 1 Largo	345 mm
Embalaje Nivel 1 Alto	170 mm
Embalaje Nivel 1 Ancho	220 mm
Embalaje Nivel 1 Unidades	1 carton

---



---

## Technical

Number of Phases	3
Grado de protección	IP20
Enclosure Type NEMA	Open Type
Frequency (f)	50/60 Hz
Input Voltage ( $U_{in}$ )	200 ... 240 V
Mounting Type	Module for cabinet building
Communication Protocol	MODBUS LON DeviceNet PROFIBUS CAN EtherNet/IP PROFINET IO TCP/IP Other Bus Systems
Number of Hardware Interfaces	Industrial Ethernet 0 PROFINET 0 RS-232 1 RS-422 0 RS-485 1 Serial TTY 0 USB 0 Parallel 0 Other 1
Includes	With control unit Without optical interface With PC connection
Analog Inputs	2
Analog Outputs	1
Number of Digital In/Outputs	5/1
Output Current, Normal Use	13.3 A
Output Power, Light-Overload Use	3 kW
Output Power, Normal Use	3 kW
Apparent Power Output	5.3 kV·A
Efficiency Level	IE2
Standby Loss	7 W
Complete Drive Module Efficiency (61800-9-2)	

Operating Point Frequency / Current	Absolute Loss	Relative Loss	Efficiency
0 / 25 %	56 W	1.1 %	83.2 %
0 / 50 %	68 W	1.3 %	88.9 %
0 / 100 %	97 W	1.8 %	91.2 %
50 / 25 %	60 W	1.1 %	90.7 %
50 / 50 %	75 W	1.4 %	93.7 %
50 / 100 %	113 W	2.1 %	94.9 %
90 / 50 %	87 W	1.6 %	95.9 %
90 / 100 %	139 W	2.6 %	96.4 %

Temperature Rating

Maximum 40 °C

## Información Adicional

Product Main Type

ACS355

Product Name

Frequency converter

## Clasificaciones

Product Series

ACS355

ETIM 7

EC001857 - Frequency converter =&lt; 1 kV

UNSPSC

39122001

## Ambiente

SCIP

619cb020-631d-4c23-9007-dec8f30bc955 Finland (FI)

Categoría RAEE

5. Small Equipment (No External Dimension More Than 50 cm)

## Where Used (as part of "kit")

Identifier	Description	Type
3AUA0000157182	ACS355-03E-13A3-2 Solar Pump Drive; ACS355-03E-13A3-2 Pn 2,2kW, I2n 13,3A IP20 Solar Pump Drive	Kit

## Categorías

Convertidores de frecuencia → Convertidores de frecuencia de baja tensión de CA → Convertidores de frecuencia para maquinaria  
→ ACS355 - Machinery Drive

